



**Liberty**  
WIRE & CABLE

**PREMADE & PATCH CABLE**

**RUN WITH US**

**HOSA TECHNOLOGY 3.5MM TRS TO 1/4" TS ADAPTER AUDIO CABLE**

1/4 inch  
ADAPTER CABLES



- Features & Benefits:**
- 1/4 inch Mono to 3.5mm Stereo Connectivity
  - Nickel-plated plugs for durability and proven performance
  - Black molded connector housings
  - Oxygen-Free Copper for enhanced signal clarity
  - OFC spiral shield for EMI rejection and flexibility
  - Available in 3, 5, and 10 feet

- CMP-100**
- Application:**
- Apply a mono signal equally to a 3.5 stereo input
  - Connect a mixing console to a portable media player
  - Connect a mixing console to a laptop or similar device

**HOSA TECHNOLOGY 3.5MM TRS TO 1/4" TRS ADAPTER AUDIO CABLE**

1/4 inch  
ADAPTER CABLES



- Features & Benefits:**
- 3.5mm Stereo to 1/4 TRS Connectivity
  - Nickel-plated plugs for durability and proven performance
  - Black Molded connector housings
  - Oxygen-Free Copper for enhanced signal clarity
  - OFC spiral shield for EMI rejection and flexibility
  - Available in 3, 5, and 10 feet

- CMS-100**
- Application:**
- Connect a portable media source to a receiver
  - Adapt 3.5mm to 1/4 or 1/4 to 3.5mm Stereo

**HOSA TECHNOLOGY DUAL 1/4" TO DUAL RCA MALE ADAPTER AUDIO CABLE**

1/4 inch  
ADAPTER CABLES



- Features & Benefits:**
- 2 1/4 inch Mono to 2 RCA Mono Connectivity
  - Nickel-plated plugs for durability & proven performance
  - Color coded molded connector housings
  - Oxygen-Free Copper for enhanced signal clarity
  - OFC spiral shield for EMI rejection and flexibility
  - Available in 1,2,3,4, and 6 meter lengths

- CPR-200**
- Application:**
- Patching & adaption equipment with 1/4 & RCA jacks
  - Connecting consumer equipment to professional gear

**HOSA TECHNOLOGY DUAL 1/4" TS TO DUAL 1/4" TS AUDIO CABLES**

1/4 inch  
NON-PLENUM



- Features & Benefits:**
- 2 1/4 inch Mono to 2 1/4 Mono Connectivity
  - Nickel-plated plugs for durability and proven performance
  - Color coded molded connector housings
  - Oxygen-Free Copper for enhanced signal clarity
  - OFC spiral shield for EMI rejection and flexibility
  - Available in 1,2,3,4, and 6 meter lengths

- CPP-200**
- Application:**
- Patching audio equipment with stereo unbalanced 1/4 jacks
  - Audio Patchbay connectivity

**HOSA TECHNOLOGY 1/4" TRS TO 1/4" TRS MALE AUDIO CABLE**

1/4 inch  
NON-PLENUM



- Features & Benefits:**
- 1/4 inch Balanced (Stereo) to same Connectivity
  - Nickel-plated plugs for durability & proven performance
  - Black molded connector housings
  - Oxygen-Free Copper for enhanced signal clarity
  - OFC spiral shield for EMI rejection and flexibility
  - Available in 3, 5, 10, 15, and 25 feet

- CSS-100**
- Application:**
- Patch and connect pro audio gear with balanced phone jacks
  - Also can be used as a 1/4 Stereo patching interconnect
  - Connect a mixing console to a laptop or similar device

**HOSA TECHNOLOGY DUAL 1/4" TRS TO DUAL 1/4" TRS MALE AUDIO CABLE**

1/4 inch  
NON-PLENUM



- Features & Benefits:**
- 2 1/4 inch Stereo to 2 1/4 Stereo Connectivity
  - Nickel-plated plugs for durability & proven performance
  - Color coded molded connector housings
  - Oxygen-Free Copper for enhanced signal clarity
  - OFC spiral shield for EMI rejection and flexibility
  - Available in 1,2,3, and 4 meter lengths

- CSS-200**
- Application:**
- Patching audio equipment with stereo balanced 1/4 jacks
  - Audio Patchbay connectivity

**MOLDED AUDIO Y CABLE ADAPTER 3.5MM STEREO MALE TO 2 RCA FEMALE 8 INCHES LONG**

3.5mm  
ADAPTER CABLES



- Features & Benefits:**
- 3.5mm Tip-Ring-Sleeve Plug (Male) to 2 RCA Jack (Female)
  - Audio "Y" Cable Breakout Adapter 8 inches long

- 35-557**
- Application:**
- iPod, MP3 Player, PC Audio breakout to Left/Right RCA
  - Adapter and Interconnection of devices into Audio routing

**HOSA TECHNOLOGY AUDIO Y CABLE ADAPTER 3.5MM STEREO FEMALE TO 2 RCA MALE 10" LONG**

3.5mm  
ADAPTER CABLES



- Features & Benefits:**
- 3.5mm Tip-Ring-Sleeve Jack (Female) to 2 RCA Plug (Male)
  - Audio "Y" Cable Breakout Adapter 10 inches long

- CFR-210**
- Application:**
- iPod, MP3 Player, PC Audio breakout to Left/Right RCA
  - Adapter and Interconnection of devices into Audio routing

**HOSA TECHNOLOGY 3.5MM TRS TO 1/4" TS ADAPTER AUDIO CABLE**

3.5mm  
ADAPTER CABLES



- Features & Benefits:**
- 1/4 inch Mono to 3.5mm Stereo Connectivity
  - Nickel-plated plugs for durability & proven performance
  - Black molded connector housings
  - Oxygen-Free Copper for enhanced signal clarity
  - OFC spiral shield for EMI rejection and flexibility
  - Available in 3, 5, and 10 feet

- CMP-100**
- Application:**
- Apply a mono signal equally to a 3.5 stereo input
  - Connect a mixing console to a portable media player
  - Connect a mixing console to a laptop or similar device

**HOSA TECHNOLOGY 3.5MM TRS TO 1/4" TRS ADAPTER AUDIO CABLE**

3.5mm  
ADAPTER CABLES



- Features & Benefits:**
- 3.5mm Stereo to 1/4 TRS Connectivity
  - Nickel-plated plugs for durability & proven performance
  - Black Molded connector housings
  - Oxygen-Free Copper for enhanced signal clarity
  - OFC spiral shield for EMI rejection and flexibility
  - Available in 3, 5, and 10 feet

- CMS-100**
- Application:**
- Connect a portable media source to a receiver
  - Adapt 3.5mm to 1/4 or 1/4 to 3.5mm Stereo

**LIBERTY 3.5MM STEREO AUDIO CABLE FOR PERMANENT INSTALLATIONS**

3.5mm  
NON-PLENUM



- Features & Benefits:**
- Nickel Plated 3 Conductor 3.5mm (1/8") Audio Plugs
  - Silver Solder termination
  - 22 AWG Twisted, shielded Broadcast Audio cable
  - UL CM, C(UL) CMG FT4, RoHS Compliant

- 221P-3.5TRSM-M**
- Application:**
- Line Level Stereo Left / Right Audio or
  - One (1) Mono Balanced Audio Channel
  - IR, RS-232C in Plenum applications

**LIBERTY RCA STEREO AUDIO TO OPEN CABLE FOR PERMANENT INSTALLATIONS**

3.5mm  
NON-PLENUM



- Features & Benefits:**
- Duplex (2) RCA Plug (male) to open connectivity
  - All Gold Plated RCA Contact Surfaces
  - Silver Solder
  - 3-inch RCA Breakout
  - NEC CMR / CL3R, CEC CMG FT4, RoHS Compliant
  - Gray Jacket

- 222P-2RCAM-T**
- Application:**
- Audio applications where install length not known
  - Audio Patching, punchdown, & terminal block installs
  - Tight Space installations and audio routing

**HOSA TECHNOLOGY 3.5MM TRS STEREO AUDIO CABLE**

3.5mm  
NON-PLENUM



**Features & Benefits:**

- Nickel-plated plugs for durability & proven performance
- Black molded connector housings
- Oxygen-Free Copper for enhanced signal clarity
- OFC spiral shield for EMI rejection and flexibility
- Available in 3,5,10, and 15 feet

**CMM-100**

**Application:**

- iPod, MP3 Player, PC Audio integration & connection
- Inter & Intra device audio interconnection
- Stage and tactical Audio patching applications

**HOSA TECHNOLOGY 3.5MM TRS STEREO AUDIO CABLE WITH ONE RIGHT ANGLE CONNECTOR**

3.5mm  
NON-PLENUM



**Features & Benefits:**

- Nickel-plated plugs for durability & proven performance
- Black molded connector housings one end 90 degrees
- Oxygen-Free Copper for enhanced signal clarity
- OFC spiral shield for EMI rejection and flexibility
- Available in 3, 5, and 10 feet

**CMM-100R**

**Application:**

- iPod, MP3 Player, PC Audio integration & connection
- Inter & Intra device audio interconnection
- Stage and tactical Audio patching applications

**HOSA TECHNOLOGY 3.5MM TRS STEREO AUDIO CABLE WITH TWO RIGHT ANGLE CONNECTORS**

3.5mm  
NON-PLENUM



**Features & Benefits:**

- Nickel-plated plugs for durability & proven performance
- Black molded connector housings both ends 90 degrees
- Oxygen-Free Copper for enhanced signal clarity
- OFC spiral shield for EMI rejection and flexibility
- Available in 3, 5, and 10 feet

**CMM-100RR**

**Application:**

- iPod, MP3 Player, PC Audio integration & connection
- Inter & Intra device audio interconnection
- Stage and tactical Audio patching applications

**HOSA TECHNOLOGY 3.5MM TRS TO 2 1/4" TS AUDIO CABLE**

3.5mm  
NON-PLENUM



**Features & Benefits:**

- 3.5mm Stereo to two 1/4 Mono Connectivity
- Nickel-plated plugs for durability & proven performance
- Molded connector housings, 1/4 inch molding color coded
- Oxygen-Free Copper for enhanced signal clarity
- OFC spiral shield for EMI rejection and flexibility
- Available in 3 and 10 feet

**CMP-150**

**Application:**

- Connect a portable media source to mixing console
- Split a Stereo 3.5 to two mono 1/4 channels

**HOSA TECHNOLOGY 3.5MM TRS TO 2 RCA MALE AUDIO CABLE**

3.5mm  
NON-PLENUM



**Features & Benefits:**

- 3.5mm Stereo to two RCA Connectivity
- Nickel-plated plugs for durability and proven performance
- Molded connector housings, RCA molding color coded
- Oxygen-Free Copper for enhanced signal clarity
- OFC spiral shield for EMI rejection and flexibility
- Available in 3,6,10,15, and 25 feet

**CMR-200**

**Application:**

- Connect a portable media source to a receiver
- Split a Stereo 3.5 to left and right RCA Audio

**LIBERTY 3.5MM STEREO AUDIO CABLE FOR PERMANENT INSTALLATIONS**

3.5mm  
NON-PLENUM



**Features & Benefits:**

- 3.5mm stereo male plug to 3.5mm stereo male connectivity
- Twisted, shielded low capacitance audio cable
- Molded green connector body
- NEC CM, CEC CMG FT4, RoHS Compliant
- Standard lengths, 3,6,12,25,35,50,75,100 feet


**E-3.5SM-M**

**Application:**

- iPod, MP3 player, PC audio integration & connection
- Inter and intra device interconnection

**LIBERTY Z100 3.5MM TRS STEREO AUDIO CABLE**

3.5mm  
NON-PLENUM



**Features & Benefits:**

- 3.5MM stereo plug (male) to 3.5mm stereo plug (male)
- All Gold Plated Contact Surfaces
- Green Molded Connector body
- Twisted pair construction with full braided copper shield
- Oxygen Free Copper Conductors and Braid Shield
- Overall Flexible PVC Jacket
- UL AWM Listed, RoHS Compliant

**Z100AM**

**Application:**

- iPod, MP3 player, PC audio, audio equipment interconnect
- Line Level Stereo Unbalanced Audio Interconnection
- Inter and Intra Device Audio Patching and routing

**LIBERTY Z100 3.5MM TRS TO 2 RCA AUDIO CABLE**

3.5mm  
NON-PLENUM



**Features & Benefits:**

- 3.5MM Stereo Plug (male) to Duplex RCA Plugs (male)
- All Gold Plated Contact Surfaces
- Molded Connector bodies with Green 3.5mm Molding
- Left and Right Labels on the RCA Plugs
- Dual Coaxial Type Construction for low loss Audio
- Oxygen Free Copper Conductors and Shields
- Siamese (SPT) Zip Construction easily separated
- UL AWM Listed, RoHS Compliant

**Z100AY**

**Application:**

- iPod, MP3 player, PC audio, consumer device interconnect
- Line Level Stereo Unbalanced Audio Interconnection
- Inter and Intra Device Audio Patching and routing

**LIBERTY MANUFACTURED 3.5MM TRS PLENUM AUDIO CABLE**

3.5mm  
PLENUM



**Features & Benefits:**

- 3.5mm Tip-Ring-Sleeve male to male connectivity
- Silver Solder
- Broadcast quality low capacitance shielded audio cable
- NEC CMP, CEC CMP FT6, RoHS Compliant

**P221P-3.5TRSM-M**

**Application:**

- Line Level stereo unbalanced audio
- Line Level Mono unbalanced Audio
- IR, RS-232C, Instrumentation and Control

**LIBERTY MANUFACTURED 3.5MM TRS TO DUPLEX RCA PLENUM AUDIO CABLE**

3.5mm  
PLENUM



**Features & Benefits:**

- 3.5mm Tip-Ring-Sleeve male to D Audio "Y" Cable
- RCA Plug (male) to Duplex RCA Plugs (male)
- All Gold Plated Contact Surfaces
- Molded connector body with blue & red silicone ID rings
- RG58 Coaxial Cable Construction for low loss Audio
- High stranding oxygen free copper conductors & shields
- Siamese (SPT) Zip Construction easily separated
- Extremely flexible soft PVC jacket
- UL AWM listed, RoHS compliant line level stereo unbalanced audio splitting
- Inter & intra device audio patching & routing duplex RCA male connectivity
- Silver Solder
- Broadcast quality low capacitance shielded audio cable
- NEC CMP, CEC CMP FT6, RoHS compliant

**P222P-3.5SM-2RCAM**

**Application:**

- Line Level stereo unbalanced audio
- Integration of mobile audio devices into L/R audio

**LIBERTY Z200 SPECIALTY AUDIO SPLITTER CABLE RCA FEMALE TO 2 RCA MALE**

RCA  
ADAPTER CABLES



- Features & Benefits:**
- Audio "Y" Cable
  - Rca jack (female) to duplex RCA plugs (male)
  - All gold plated contact surfaces
  - Molded connector body with blue & red silicone ID rings
  - RG58 coaxial cable construction for low loss audio
  - High stranding oxygen free copper conductors & shields
  - Siamese (SPT) zip construction easily separated
  - Extremely flexible soft PVC jacket
  - UL AWM listed, rohs compliant

**Z200FM**  
**Application:**

- Line level stereo unbalanced audio splitting
- Inter & intra device audio patching & routing

**LIBERTY Z200 SPECIALTY AUDIO SPLITTER CABLE RCA MALE TO 2 RCA FEMALE**

RCA  
ADAPTER CABLES



- Features & Benefits:**
- Audio "y" cable
  - RCA Male (male) to Duplex RCA Jacks (female)
  - All gold plated contact surfaces
  - Molded connector body with blue & red silicone ID rings
  - Rg58 coaxial cable construction for low loss audio
  - High stranding oxygen free copper conductors & shields
  - Siamese (SPT) zip construction easily separated
  - Extremely flexible soft PVC jacket
  - UL AWM listed, rohs compliant

**Z200MF**  
**Application:**

- Line level stereo unbalanced audio splitting
- Inter & intra device audio patching & routing

**LIBERTY Z200 SPECIALTY AUDIO SPLITTER CABLE RCA MALE TO 2 RCA MALE**

RCA  
ADAPTER CABLES



- Features & Benefits:**
- Audio "y" cable
  - RCA Plug (male) to Duplex RCA Plugs (male)
  - All gold plated contact surfaces
  - Molded connector body with blue & red silicone ID rings
  - Rg58 coaxial cable construction for low loss audio
  - High stranding oxygen free copper conductors & shields
  - Siamese (SPT) zip construction easily separated
  - Extremely flexible soft PVC jacket
  - UL AWM listed, rohs compliant

**Z200MM**  
**Application:**

- Line level stereo unbalanced audio splitting
- Inter & intra device audio patching & routing

**HOSA TECHNOLOGY DUAL RCA TO DUAL RCA MALE AUDIO CABLE**

RCA  
NON-PLENUM



- Features & Benefits:**
- 2 RCA Mono to 2 RCA Stereo Connectivity
  - Nickel-plated plugs for durability and proven performance
  - Color coded molded connector housings
  - Oxygen-Free Copper for enhanced signal clarity
  - OFC spiral shield for EMI rejection and flexibility
  - Available in 1,2,3,4, and 6 meter lengths

**CRA-200**  
**Application:**

- Patching equipment with Stereo RCA jacks
- Connecting consumer equipment to professional gear

**LIBERTY DUPLEX RCA AUDIO CABLE FOR PERMANENT INSTALLATIONS**

RCA  
NON-PLENUM

**Features & Benefits:**

**E-2RCAM-M**

**Application:**

NOTHING ON LINE?

**LIBERTY Z100 DUPLEX RCA STEREO AUDIO CABLE**

RCA  
NON-PLENUM



**Features & Benefits:**

- Duplex RCA plugs (male) to duplex RCA plugs (male)
- All gold plated contact surfaces
- Molded connector body with left & right labels
- Dual coaxial type construction for low loss audio
- oxygen free copper conductors and shields
- Siamese (SPT) zip construction easily separated
- UL AWM listed, RoHS compliant


**Z100A**

**Application:**

- Line level stereo unbalanced audio interconnection
- Inter and Intra Device Audio Patching and routing

**LIBERTY Z200 DUPLEX RCA AUDIO CABLE**

RCA  
NON-PLENUM



**Features & Benefits:**

- Duplex RCA plugs (male) to duplex RCA plugs (male)
- All gold plated contact surfaces
- Molded connector body with blue & red silicone id rings
- RG58 coaxial cable construction for low loss audio
- High stranding oxygen free copper conductors & shields
- Siamese (SPT) zip construction easily separated
- Extremely flexible soft PVC jacket
- UL AWM listed, RoHS compliant

**Z200A**

**Application:**

- Line Level Stereo Unbalanced Audio Interconnection
- Inter and Intra Device Audio Patching and routing

**LIBERTY Z250 DUPLEX RCA AUDIO CABLE**

RCA  
NON-PLENUM



**Features & Benefits:**

- Duplex RCA plugs (male) to duplex RCA plugs (male)
- All gold plated contact surfaces
- Audiophile metal RCA body with blue and red ID labels
- RG58 coaxial cable construction for low loss audio
- High stranding oxygen free copper conductors & shields
- Siamese (SPT) zip construction easily separated
- Extremely flexible soft PVC jacket
- UL AWM Listed, RoHS compliant

**Z250A**

**Application:**

- Line Level Stereo Unbalanced Audio Interconnection
- Inter and Intra Device Audio Patching and routing



**LIBERTY MANUFACTURED DUPLEX RCA PLENUM AUDIO CABLE**

RCA  
PLENUM



**Features & Benefits:**

- Metal shelled Gold plated contact RCA plugs
- Silver Solder
- 22 AWG Twisted, shielded Broadcast Audio cable
- UL CMP, C(UL) CMP FT6, RoHS Compliant

**P222P-2RCAM-M**

**Application:**

- Line Level Stereo Left / Right Audio Channels
- Plenum stereo unbalanced audio applications

**LIBERTY MANUFACTURED DUPLEX RCA TO OPEN END PLENUM AUDIO CABLE**

RCA  
PLENUM



**Features & Benefits:**  
NO Features on WEB

**P222P-2RCAM-T**

**Application:**

**HOSA TECHNOLOGY XLR 3-PIN FEMALE TO PHOENIX 3-PIN MALE ADAPTER CABLE 6"**

XLR  
ADAPTER CABLES



**Features & Benefits:**

- XLR 3-Pin female to Phoenix 3-pin male connectivity
- Short adapter cable 6 inch cable length

**PHX-100F**  
**Application:**

- Connecting bare wire to gear with XLR inputs
- Audio adaption and wiring

**HOSA TECHNOLOGY XLR 3-PIN MALE TO PHOENIX 3-PIN MALE ADAPTER CABLE 6"**

XLR  
ADAPTER CABLES



**Features & Benefits:**

- XLR 3-Pin male to Phoenix 3-pin male connectivity
- Short adapter cable 6 inch cable length

**PHX-100M**  
**Application:**

- Connecting bare wire to gear with XLR outputs
- Audio adaption and wiring

**HOSA TECHNOLOGY XLR 3-PIN FEMALE TO PHOENIX 3-PIN FEMALE ADAPTER CABLE 6"**

XLR  
ADAPTER CABLES



**Features & Benefits:**

- XLR 3-Pin female to Phoenix 3-pin female connectivity
- Short adapter cable 6 inch cable length

**PHX-200F**  
**Application:**

- Connecting bare wire to gear with XLR inputs
- Audio adaption and wiring

**HOSA TECHNOLOGY XLR 3-PIN MALE TO PHOENIX 3-PIN FEMALE ADAPTER CABLE 6"**

XLR  
ADAPTER CABLES



**Features & Benefits:**

- XLR 3-Pin male to Phoenix 3-pin female connectivity
- Short adapter cable 6 inch cable length

**PHX-200M**  
**Application:**

- Connecting bare wire to gear with XLR outputs
- Audio adaption and wiring

**HOSA TECHNOLOGY XLR 3-PIN FEMALE TO 1/4" TRS MALE ADAPTER CABLE**

XLR  
ADAPTER CABLES



**Features & Benefits:**

- XLR 3-Pin female to 1/4 TRS male Connectivity
- Nickel-plating for durability and signal transfer
- Oxygen-Free Copper for enhanced signal clarity
- OFC spiral shield for EMI rejection and flexibility
- Available lengths: 3,5,10,15, and 20 feet

**STX-100F**  
**Application:**

- Connect XLR outputs to gear with balanced phone inputs
- Ideal for a variety of Pro-Audio

**HOSA TECHNOLOGY XLR 3-PIN MALE TO 1/4" TRS MALE ADAPTER CABLE**

**XLR  
ADAPTER CABLES**



- Features & Benefits:**
- XLR 3-Pin male to 1/4 TRS male Connectivity
  - Nickel-plating for durability and signal transfer
  - Oxygen-Free Copper for enhanced signal clarity
  - OFC spiral shield for EMI rejection and flexibility
  - Available lengths: 3,5,10,15, and 20 feet

**STX-100M**

- Application:**
- Connect XLR inputs to gear with balanced phone outputs
  - Ideal for a variety of Pro-Audio

**ATLAS SOUND TACTICAL MICROPHONE AND BALANCED AUDIO XLR CABLES**

**XLR  
NON-PLENUM**



- Features & Benefits:**
- XLR 3-Pin Plug (Male) to XLR 3-Pin Jack (Female)
  - Custom molded Sure Grip Connectors
  - Oxygen free copper conductors
  - Class II shielding and a PolyFlex outer jacket

**AS2XLR**

- Application:**
- Microphone level audio, Line Level MONO Balanced Audio
  - Line Level Stereo Unbalanced Audio
  - Device interconnection of audio systems

**HOSA EDGE XLR MICROPHONE CABLES**

**XLR  
NON-PLENUM**



- Features & Benefits:**
- Original Neutrik connectors for security and durability
  - 20 AWG Oxygen-Free Copper for maximum signal transfer
  - Low capacitance for crystal-clear highs and lows
  - Durable and designed for stage and tactical use
  - Available in 3,5,10,15,20,25,30,50,75 and 100 feet

**CMK-**

- Application:**
- Microphone level audio, Line Level MONO Balanced Audio
  - Line Level Stereo Unbalanced Audio
  - Tactical and high movement Audio and Mic patching

**HOSA TECHNOLOGY DMX-512 XLR 5-PIN MALE TO XLR 5-PIN FEMALE 120-OHM CABLES**

**XLR  
NON-PLENUM**



- Features & Benefits:**
- XLR 5-pin male to XLR 5-pin female Connectivity
  - Nickel-plated plugs for durability and proven performance
  - Oxygen-Free Copper for enhanced signal clarity
  - OFC spiral shield for EMI rejection and flexibility
  - 110-Ohm Impedance for RS-485/DMX-512 Signals
  - Available in 3,5,10,20,25,30,50, and 100 feet

**DMX-500**

- Application:**
- DMX-512 Control and Communications
  - Stage Lighting and Digital Effects patching

**HOSA TECHNOLOGY AES/EBU XLR 3-PIN MALE TO XLR 3-PIN FEMALE 100-OHM CABLES**

**XLR  
NON-PLENUM**



**Features & Benefits:**

- XLR 3-pin Male to XLR 3-pin Female Connectivity
- Metal shelled XLR's with internal strain relief
- 24 AWG 110-Ohm shielded Digital Audio Cable
- OFC Braided shield for EMI rejection
- Cable is black in color
- Available in 3,5,10,15,20,25,30,50 and 100 foot lengths

**EBU-**

**Application:**

- AES/EBU Digital Audio interconnection and patching
- Also excellent for balanced analog audio

**HOSA TECHNOLOGY PRO MICROPHONE XLR 3-PIN MALE TO FEMALE CABLES**

**XLR  
NON-PLENUM**



**Features & Benefits:**

- XLR 3-pin male to XLR 3-pin female connectivity
- Silver-plated REAN connectors for superior signal transfer
- 20 AWG Oxygen-Free Copper for a louder, clearer signal
- 90% OFC braided shield for a higher signal to noise ratio
- Balanced format
- Available lengths: 3,5,10,15,20,25,30,50, and 100 feet

**HMIC-**

**Application:**

- Microphone level audio, Line Level MONO Balanced Audio
- Line Level Stereo Unbalanced Audio
- Tactical and high movement Audio and Mic patching

**LIBERTY VGA AND PC AUDIO WITH TRIPLEX AUDIO/VIDEO RCA COMBINATION CABLE**

Audio / Video Cables  
NON-PLENUM



**Features & Benefits:**

- 2 Video channels & 2 Audio channels under one jacket
- De15 male (VGA) to de15 male (VGA) ID/DDC compliant video
- RCA Composite Video to RCA Composite Video
- 3.5mm Stereo Mini male to 3.5mm Stereo Audio male Audio
- Left & right RCA male to left & right RCA male audio
- 26 AWG 200 MHz stranded mini-high res coaxial cables
- NEC CL2, CEC CMG FT4, RoHS compliant

**E-2V2AC3**

**Application:**

- Single Faceplate support for 2 video and 2 audio channels
- Podium Single cable hookup for presentation systems

**LIBERTY VGA AND PC AUDIO WITH COMPOSITE VIDEO RCA COMBINATION CABLE**

Audio / Video Cables



**Features & Benefits:**

- 75 OHM 200 MHz Bandwidth Multi-Coaxial RGB PVC Interconnect cable
- VGA & composite video and 3.5 mm stereo plug to VGA & composite video and 3.5 mm stereo plug 100 ft

**F-2V1A**

**Application:**

- NA

**LIBERTY VGA AND PC AUDIO WITH TRIPLEX A/V RCA COMBINATION CABLE**

Audio / Video Cables  
NON-PLENUM



**Features & Benefits:**

- NA

**F-2V2A-C4**

**Application:**

- NA

**LIBERTY Z100 TRIPLEX RCA AUDIO/VIDEO CABLE**

Audio / Video Cables  
NON-PLENUM



**Features & Benefits:**

- All Gold Plated Contact Surfaces
- Bulk cable coaxial formats
- Triplex type construction, easy separation to customize

**OSZ100AV**

**Application:**

- RCA Composite Video and Left Right RCA Audio
- Device to Device and Device to Plate interconnection
- Not for In-wall unless in conduit

**LIBERTY Z100 TRIPLEX RCA AUDIO/VIDEO CABLE**

Audio / Video Cables  
NON-PLENUM



**Features & Benefits:**

- All Gold Plated Contact Surfaces
- Economical Oxygen Free Copper Bulk cable coaxial formats
- Silver Solder
- UL AWM ratings UL20276 for Class 2 device Interconnection
- Triplex type construction, easy separation to customize

**Z100AV**

**Application:**

- RCA Composite Video and Left Right RCA Audio
- Device to Device and Device to Plate interconnection
- Not for In-wall unless in conduit

**LIBERTY Z200 TRIPLEX RCA AUDIO/VIDEO CABLE**

Audio / Video Cables  
NON-PLENUM



**Features & Benefits:**

- Triplex RCA Plugs (male) to Triplex RCA Plugs (male)
- All Gold Plated Contact Surfaces
- Molded RCA body with blue, red, yellow id labels
- RG58 Coaxial Cable Construction for low loss Audio
- RG59 75-Ohm Video Coaxial Cable for the Yellow Leg
- High stranding oxygen free copper conductors & shields
- Siamese (SPT) Zip Construction easily separated
- Extremely flexible soft PVC jacket
- UL AWM Listed, RoHS Compliant

**Z200AV**

**Application:**

- Stereo Unbalanced Audio & Video Interconnection
- Inter & Intra Device Audio Patching & routing

**LIBERTY Z250 TRIPLEX RCA AUDIO/VIDEO CABLE**

Audio / Video Cables  
NON-PLENUM



**Features & Benefits:**

- Triplex RCA Plugs (male) to Triplex RCA Plugs (male)
- All Gold Plated Contact Surfaces
- Audiophile metal RCA body with blue, red, yellow ID labels
- RG58 Coaxial Cable Construction for low loss Audio
- RG59 75-Ohm Video Coaxial Cable for the Yellow Leg
- High stranding oxygen free copper conductors & shields
- Siamese (SPT) Zip Construction easily separated
- Extremely flexible soft PVC jacket
- UL AWM Listed, RoHS Compliant


**Z250AV**

**Application:**

- Stereo Unbalanced Audio and Video Interconnection
- Inter and Intra Device Audio Patching & routing

**LIBERTY MANUFACTURED PLENUM RATED AUDIO/VIDEO TRIPLEX RCA CABLE**

Audio / Video Cables  
PLENUM



**Features & Benefits:**

- 3 RCA Male to 3 RCA Male Connectivity
- Gold Pin Crimp MHR RCA Plugs
- Crimp Termination has better frequency response
- Red, White, Yellow Color coded sub-cables with boots
- 26 AWG mini-High resolution 200 MHz bandwidth Coax cables
- NEC CMP/CL2P, CEC CMP FT6, RoHS Compliant

**D-AV3RCAM-M**

**Application:**

- Audio/Video Triplex Composite Video and Left/Right Audio
- 3 Composite Video Feeds, S/PDIF Digital Audio, IR Trigger

### 25FT CAT5E / CAT5 350MHZ SNAGLESS PATCH CABLE RJ45 M/M WHITE 25'

Category / LAN / Data Patch Cables  
NON-PLENUM



#### Features & Benefits:

- Cat5e 350MHz Snagless Molded Patch Cable, 25ft - White
- Premium cabling for Category 5 and 5e applications
- Rated for 350 MHz/1 Gbps communications
- Feature molded connectors with integral strain relief
- Meets most current industry standards

#### N001-025-WH

#### Application:

- LAN 10/100/1000BaseT Ethernet Patching, Balun Support
- OEM Systems Device interconnection, touch panels
- IP Control, Voice, Voice over IP, Video

### LAN AND HDBASET SOLUTIONS SHIELDED CATEGORY 6A PRE-MADE PATCH CABLE

Category / LAN / Data Patch Cables  
NON-PLENUM



#### Features & Benefits:

- Category 6 F/UTP shielded stranded patch cable
- 8P8C modular RJ45 plugs with gold flash plated contacts
- Strain relief boots as required by 568 standard
- Factory tested to ANSI/TIA-568C Cat6 patch cable
- UL listed AWM, RoHS compliant
- Standard lengths are 1,3,5,7,10,14, and 25 feet
- Custom lengths available upon request

#### PC6ABS

#### Application:

- LAN 10/100/1000BaseT Ethernet Patching, Balun Support
- OEM Systems Device interconnection, touch panels
- IP Control, Voice, Voice over IP, Video, HDBaseT

### LAN SOLUTIONS CATEGORY 6 U/UTP PRE-MADE PATCH CABLE

Category / LAN / Data Patch Cables  
NON-PLENUM



#### Features & Benefits:

- RJ45 8P8C Plug (Male) to RJ45 8P8C Plug (Male) Connectivity
- Strain relief boots per ANSI/TIA/EIA-568 Requirements
- U/UTP Stranded Patch Cable
- UL Listed AWM, ANSI/TIA/EIA-568 Category 6 Compliant
- Standard Lengths 1,3,5,7,10,14,25 Feet per standard
- Other lengths available upon request at a premium

#### PC6B0

#### Application:

- LAN 10/100/1000BaseT Ethernet Patching, Balun Support
- OEM Systems Device interconnection, touch panels
- IP Control, Voice, Voice over IP, Video

### LAN AND HDBASET SOLUTIONS SHIELDED CATEGORY 6 PRE-MADE PATCH CABLE

Category / LAN / Data Patch Cables  
NON-PLENUM



#### Features & Benefits:

- Category 6 F/UTP shielded stranded patch cable
- 8P8C modular RJ45 plugs with gold flash plated contacts
- Strain relief boots as required by 568 standard
- Factory tested to ANSI/TIA-568C Cat6 patch cable
- UL listed AWM, RoHS compliant
- Standard lengths are 1,3,5,7,10,14, and 25 feet
- Custom lengths available upon request

#### PC6BS

#### Application:

- LAN 10/100/1000BaseT Ethernet Patching, Balun Support
- OEM Systems Device interconnection, touch panels
- IP Control, Voice, Voice over IP, Video, HDBaseT

**LAN SOLUTIONS CATEGORY 5E U/UTP PRE-MADE PATCH CABLE**

Category / LAN / Data Patch Cables  
NON-PLENUM



**Features & Benefits:**

- RJ45 8P8C Plug (Male) to RJ45 8P8C Plug (Male) Connectivity
- Strain relief boots per ANSI/TIA/EIA-568 Requirements
- U/UTP Stranded Patch Cable
- UL Listed AWM, ANSI/TIA/EIA-568 Category 5e Compliant
- Standard Lengths 1,3,5,7,10,14,25 Feet per standard.
- Other lengths available upon request at a premium

**PCE5B0**

**Application:**

- LAN 10/100/1000BaseT ethernet patching, Balun support
- OEM Systems Device interconnection, touch panels
- IP Control, Voice, Voice over IP, Video

**LAN SOLUTIONS SHIELDED CATEGORY 5E PRE-MADE PATCH CABLE**

Category / LAN / Data Patch Cables  
NON-PLENUM



**Features & Benefits:**

- Category 5 F/UTP stranded shielded patch cable
- Shielded 8P8C modular RJ45 plugs
- Strain relief boots
- Factory tested to ANSI/TIA-568C Cat5E patch cable
- UL listed AWM, RoHS compliant
- Standard lengths are 1,3,5,7,10,14, and 25 feet
- Custom lengths available upon request

**PCE5BS**

**Application:**

- LAN 10/100/1000BaseT ethernet patching, Balun support
- OEM Systems Device interconnection, touch panels
- HDBaseT multimedia patching and routing
- IP Control, Voice, Voice over IP, Video

**LAN AND HDBASET SOLUTIONS SHIELDED CATEGORY 6A PRE-MADE PLENUM PATCH CABLE**

Category / LAN / Data Patch Cables  
PLENUM



**Features & Benefits:**

- Category 6A F/UTP shielded solid plenum rated cable
- 8P8C modular RJ45 plugs with gold flash plated contacts
- Strain relief boots as required by 568 standard
- Tested to ANSI/TIA-568C Cat6A on Fluke DTX-1800
- NEC CMP, CEC CMP FT6, RoHS compliant
- Standard lengths: 35,50,75,100,150,200,250 and 300 feet
- Custom lengths available upon request

**PPC6ABS**

**Application:**

- LAN 10/100/1000/10GBaseT ethernet runs and balun support
- Pre-terminated cables for HDBaseT runs
- IP Control, Voice, Voice over IP, Video, HDBaseT

**LAN SOLUTIONS CATEGORY 6 U/UTP PRE-MADE PLENUM PATCH CABLE**

Category / LAN / Data Patch Cables  
PLENUM



**Features & Benefits:**

- RJ45 8P8C Plug (Male) to RJ45 8P8C Plug (Male) Connectors
- Strain relief boots per ANSI/TIA/EIA-568 Requirements
- Base cable is SOLID U/UTP Category 6
- NEC CMP, CEC CMP FT6, TIA/EIA-568 Category 6 Compliant
- Standard Lengths 1,3,5,7,10,14,25 Feet per standard.
- Other lengths available upon request at a premium

**PPC6B0**

**Application:**

- LAN 10/100/1000BaseT Ethernet Patching, Balun Support
- OEM Systems Device interconnection, touch panels
- IP Control, Voice, Voice over IP, Video



### LAN AND HDBASET SOLUTIONS SHIELDED CATEGORY 6 PRE-MADE PLENUM PATCH CABLE

Category / LAN / Data Patch Cables

**PLENUM**



#### Features & Benefits:

- Category 6 F/UTP shielded solid plenum rated cable
- 8P8C modular RJ45 plugs with gold flash plated contacts
- Strain relief boots as required by 568 standard
- Tested to ANSI/TIA-568C Cat6 on Fluke DTX-1800
- NEC CMP, CEC CMP FT6, RoHS compliant
- Standard lengths: 35,50,75,100,150,200,250 and 300 feet
- Custom lengths available upon request

#### PPC6BS

#### Application:

- LAN 10/100/1000BaseT ethernet runs and Balun support
- Pre-terminated cables for HDBaseT runs
- IP Control, Voice, Voice over IP, Video, HDBaseT

### LAN SOLUTIONS CATEGORY 5E U/UTP PRE-MADE PLENUM PATCH CABLE

Category / LAN / Data Patch Cables

**PLENUM**



#### Features & Benefits:

- RJ45 8P8C plug (male) to RJ45 8P8C plug (male) connection
- Strain relief boots per ANSI/TIA/EIA-568 requirements
- U/UTP solid cable
- NEC CMP, CEC CMP FT6, ANSI/TIA/EIA-568 Category 5e
- Standard lengths 1,3,5,7,10,14,25 feet per standard.
- Other lengths available upon request at a premium

#### PPCE5B

#### Application:

- LAN 10/100/1000BaseT ethernet patching, Balun support
- OEM Systems Device interconnection, touch panels
- HDBaseT multimedia patching and routing
- IP Control, Voice, Voice over IP, Video

### LAN SOLUTIONS SHIELDED CATEGORY 5E PRE-MADE PLENUM PATCH CABLE

Category / LAN / Data Patch Cables

**PLENUM**



#### Features & Benefits:

- RJ45 8P8C plug (male) to RJ45 8P8C plug (male) connection
- Strain relief boots per ANSI/TIA/EIA-568 Requirements
- F/UTP Shielded Solid Cable
- NEC CMP, CEC CMP FT6, ANSI/TIA/EIA-568 Category 5e
- Standard Lengths 1,3,5,7,10,14,25 Feet per standard.
- Other lengths available upon request at a premium

#### PPCE5BS

#### Application:

- LAN 10/100/1000BaseT ethernet patching, Balun support
- OEM Systems Device interconnection, touch panels
- IP Control, Voice, Voice over IP, Video

**LIBERTY MANUFACTURED 450MHZ COMPONENT VIDEO INTERCONNECTOR LISTED FOR IN-WALL USE**

Component Video Cables  
NON-PLENUM



**Features & Benefits:**

- 3 RCA Male Plug to 3 RCA Male Plug Connectivity
- Video on 25 AWG Mini-RG59 coaxial cables
- 450 MHz bandwidth coaxial cables
- NEC CMR, CEC CMG FT4, RoHS Compliant

**B-3RCAM-M**

**Application:**

- Component Video, A/V RCA Triplex, S/PDIF and Analog L/R
- Inter and Intra device interconnection

**LIBERTY MANUFACTURED HD15 TO 3 RCA COMPONENT VIDEO INTERFACE CABLE**

Component Video Cables

NON-PLENUM



**Features & Benefits:**

- VGA Male Plug to 3 RCA Male Plug Connectivity
- Video on 25 AWG mini-RG59 coaxial cables
- 450 MHz Bandwidth coaxial legs
- Cable does not convert signal
- NEC CMR, CEC CMG FT4, RoHS Compliant

**B-VGAM-3RCAM**


**Application:**

- Component Video output from an HD15 Component source
- Inter and Intra device interconnection

**LIBERTY MANUFACTURED 450MHZ COMPONENT VIDEO INTERCONNECTOR LISTED FOR IN-WALL USE**

Component Video Cables

NON-PLENUM



**Features & Benefits:**

- NA

**BB-3RCAM-M**

**Application:**

- NA

**LIBERTY MOLDED COMPONENT VIDEO INTERCONNECT LISTED FOR IN-WALL USE**

Component Video Cables

NON-PLENUM



**Features & Benefits:**

- Liberty's molded assemblies feature robust dual shielded 26 AWG mini High Resolution coaxial cables for
- excellent performance and bandwidth. This is a Molded
- Component Video cable terminated in 75 Ohm BNC plugs. The
- cable is rated CL2 in the US and CMG FT4 for Canadian
- in-wall installations. This can also be utilized for
- Composite Video, S-Video and Digital Audio applications.

**E-3BNCM-M**

**Application:**

- NA

**LIBERTY MOLDED COMPONENT VIDEO INTERCONNECT LISTED FOR IN-WALL USE**

Component Video Cables

NON-PLENUM



**Features & Benefits:**

- 3 RCA Male Plug to 3 RCA Male Plug Connectivity
- Video on 26 AWG high resolution coaxial cables
- Molded 'Hand' Strain relief breakout
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant
- Standard Lengths, 1,3,6,10,15,25,35,50,75,100 feet

**E-3RCAM-M**

**Application:**

- Component Video, A/V RCA Triplex, S/PDIF and Analog L/R
- Inter and Intra device interconnection

**COMPONENT VIDEO TO VGA ADAPTOR CABLE FOR USE WITH FLX-RI4 CARDS**

Component Video Cables  
NON-PLENUM



- Features & Benefits:**
- Female RCA connectors for YPbPr connection.
  - Male HD15 connector for FLX-RI4 inputs.

**FLX-RBOCA**

- Application:**
- Connecting DVD, SAT/CBL, or any other component video source to the scaler input (FLX-RI4) of a FLX modular matrix

**LIBERTY Z100 ECONOMY MOLDED COMPONENT VIDEO INTERCONNECT FOR NON IN-WALL USE**

Component Video Cables  
NON-PLENUM




- Features & Benefits:**
- All Gold Plated Contact Surfaces
  - Economical Oxygen Free Copper Bulk cable coaxial formats
  - Silver Solder
  - UL AWM ratings UL20276 for Class 2 device Interconnection
  - Triplex type construction, easy separation to customize

**Z100CV**

- Application:**
- RCA Component Y,Pb,Pr Video or A/V Triplex RCA
  - Device to Device and Device to Plate interconnection
  - Not for In-wall unless in conduit

**LIBERTY Z250 TRIPLEX RCA COMPONENT VIDEO CABLE**

Component Video Cables  
NON-PLENUM



- Features & Benefits:**
- Triplex RCA Plugs (male) to Triplex RCA Plugs (male)
  - All Gold Plated Contact Surfaces
  - Audiophile Metal RCA Body with Green, Red, Blue ID labels
  - RG59 75-Ohm Video Coaxial Cable
  - High Stranding Oxygen Free Copper Conductors and Shields
  - Siamese (SPT) Zip Construction easily separated
  - Extremely flexible soft PVC jacket
  - UL AWM Listed, RoHS Compliant

**Z250CV**

- Application:**
- Component Video Y,Pb,Pr patching and routing
  - Standard and High Definition Y,Pb,Pr Video Interconnection
  - Inter and Intra Device Video Patching and routing

**THX® CERTIFIED HOME THEATER GRADE COMPONENT VIDEO INTERCONNECT FOR NON IN-WALL USE**

Component Video Cables  
NON-PLENUM




- Features & Benefits:**
- Triplex RCA Y,Pb,Pr male to male connectivity
  - All Gold plated contact surfaces
  - High strand Oxygen Free 75 Ohm RG59 Coaxial cables
  - THX Certification
  - Discontinued, when stock is gone there is no more

**Z300NCVTHX**

- Application:**
- Home Theater Component Video (Y,Pb,Pr)
  - Can also be used for Digital Audio, A/V triplex RC

**THX® CERTIFIED HOME THEATER GRADE COMPONENT VIDEO INTERCONNECT FOR NON IN-WALL USE**

Component Video Cables  
NON-PLENUM



- Features & Benefits:**
- Triplex RCA Y,Pb,Pr male to male connectivity
  - All Gold plated contact surfaces
  - High strand Oxygen Free 75 Ohm RG59 Coaxial cables
  - THX Certification
  - Discontinued, when stock is gone there is no more

**Z400NCVTHX**

- Application:**
- Home Theater Component Video (Y,Pb,Pr)
  - Can also be used for Digital Audio, A/V triplex RCA

**THX® CERTIFIED HOME THEATER GRADE COMPONENT VIDEO INTERCONNECT FOR NON IN-WALL USE**

Component Video Cables

NON-PLENUM



**Features & Benefits:**

- Gold Plated RCA plugs with Pearl white enamel
- Green, Blue, Red banded for Y,Pb,Pr
- Silver Solder and Ohno-Continuous Cast Copper (OCC)
- Dual Shielded for low and high frequency use
- Polypropylene silk mesh overall jacket
- Available in 2.0, 3.0, and 4.0 meters

**Z500NCVTHX**

**Application:**

- Component Video, Triplex Audio Video RCA
- Home Theater, High End Video

**LIBERTY MANUFACTURED TRIPLEX RCA PLENUM RATED COMPONENT VIDEO CABLE**

Component Video Cables

PLENUM



**Features & Benefits:**

- 3 RCA Male to 3 RCA Male Connectivity
- Gold Pin Crimp MHR RCA Plugs
- Crimp Termination has better frequency response
- Red, Green, Blue Color coded sub-cables with boots
- 26 AWG mini-High resolution 200 MHz bandwidth Coax cables
- NEC CMP/CL2P, CEC CMP FT6, RoHS Compliant

**D-3RCAM-M**

**Application:**

- Y,Pb,Pr Component Video and HD Component Video
- Composite Video, Left / Right RCA Analog Audio
- S-Video, InfraRed Trigger, S/PDIF Digital Audio

**PS2 MOUSE AND KEYBOARD INTERCONNECTION CABLE**

Computer

NON-PLENUM



FPO

**Features & Benefits:**

- Beige Molded Connectors and Cable
- Mini DIN 6Pin Plug (Male) to Mini DIN 6Pin Plug (Male)
- UL AWM Rated cable, not for in-wall use unless in conduit

**10M2-011**

**Application:**

- Connection of PS2 format devices
- Keyboard, Mouse, KVM, Control interface cable

**LIBERTY PREMIUM MOLDED DVI ANALOG TO 5 BNC FEMALE CABLE**

DVI Cables

ADAPTER CABLES



**Features & Benefits:**

- Male DVI Plug to 5 BNC Jack (Female) Connectivity
- 26 AWG Stranded mini-High Resolution Coaxial cables
- 75 Ohm BNC Jacks
- Durable heavy duty molding and strain relief
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-DVI/A-5BNCF**

**Application:**

- DVI Analog Only conversion to 5-wire RGBHV
- RGBHV Video breakout to larger low loss coaxial cables
- Installations where RGBHV has to go through conduit

**LIBERTY PREMIUM MOLDED DVI ANALOG TO 5 BNC MALE CABLE**

DVI Cables

ADAPTER CABLES



**Features & Benefits:**

- Male DVI Plug to 5 BNC Pack (male) Connectivity
- 26 AWG Stranded mini-High Resolution Coaxial cables
- 75 Ohm BNC Plugs
- Durable heavy duty molding and strain relief
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-DVI/A-5BNCM**

**Application:**

- DVI Analog Only conversion to 5-wire RGBHV
- RGBHV Video breakout to larger low loss coaxial cables
- Installations where RGBHV has to go through conduit

**LIBERTY PREMIUM MOLDED DVI ANALOG TO VGA MALE CABLE**

DVI Cables

ADAPTER CABLES



**Features & Benefits:**

- DVI/A Plug to DE15 (VGA) Male Connectivity
- UL AWM rated cabling
- Economy product, basic construction

**E-DVI/A-VGAM**

**Application:**

- Analog RGBHV from DVI-I output to VGA Display

**LIBERTY PREMIUM MOLDED DVI DIGITAL DUAL LINK CABLE**

DVI Cables

ADAPTER CABLES



**Features & Benefits:**

- DVI Dual Link Digital 29pin Plugs
- 28 AWG TMDS Pair Construction
- Reduced DVI molding for high density bays
- UL CL2 and CSA FT4 for In-wall, RoHS Compliant
- Resolutions up to 2048x1536 QXGA supported

**E-DVIDDL**

**Application:**

- Video Wall, Computer Monitor, HDTV, CAD Station
- In-wall DVI-D Video Routing

**LIBERTY PREMIUM MOLDED DVI DIGITAL SINGLE LINK CABLE**

DVI Cables

ADAPTER CABLES



**Features & Benefits:**

- DVI 1.0 Single Link Digital Connectivity (19-pin)
- 28 AWG TMDS Pair Construction
- Triple Shielded Cable Construction
- Reduced DVI molding for high density bays
- NEC CL2 and CEC FT4 for In-wall use, RoHS Compliant
- DVI 1.0 5.0 Gbps / 1900x1200 WUXGA / 1080p60

**E-DVIDSL**

**Application:**

- Video Wall, Computer Monitor, HDTV, CAD Station
- In-wall DVI-D Video Routing

**50FT DVI DUAL LINK TMDS CABLE MOLDED SHIELDED DVI-D M/M 50'**

DVI Cables  
NON-PLENUM



- Features & Benefits:**
- 50ft. DVI-D dual link cable, digital TMDS monitor cable
  - For use with Dual or Single Link TMDS specified equipment
  - Provides bandwidth for resolutions up to 2560 x 1600
  - High Speed Digital Transmission to 9.9Gbps
  - Superior molded cables with foil/braid shielding

**P560-050**  
**Application:**

- Ideal for home, office applications
- Video wall, computer monitor, HDTV, CAD station

**LIBERTY Z400 DVI DUAL LINK 12 METER CABLES**

DVI Cables  
NON-PLENUM



- Features & Benefits:**
- DVI Dual Link Digital 29pin Plugs
  - 24 AWG TMDS Pair Construction
  - UL CL2 & CSA FT4 for In-wall, RoHS Compliant
  - Resolutions up to 2048x1536 QXGA supported

**P560-050**  
**Application:**

- Video wall, computer monitor, HDTV, CAD station

**CELERITY DETACHABLE FIBER OPTIC PLENUM DVI SINGLE LINK INTERCONNECTION CABLES**

DVI Cables  
PLENUM



- Features & Benefits:**
- Plenum rated cable for all installations
  - Ultra-small diameter cable
  - Detachable DVI TX and RX units from main body
  - USB Power A plug on both TX and RX units
  - TX end only needs USB power if LED does not light up
  - Lengths: 40, 60, 80, 100, 160, 200, 500, 1000 ft
  - DVI Single Link Video with HDCP support

**DFO-DVI**  
**Application:**

- DVI video & audio for projectors & displays
- Maximum bandwidth and distance for DVI installs

**ECONOMY MOLDED D-SUB RS-232 AND CONTROL CABLE**

Data & Control Cables

NON-PLENUM



**Features & Benefits:**

- D-SUB DE09 Jack (Female) to DE09 Jack (Female) Connectors
- Straight through pin out 1-1, 2-2, etc.
- Molded housings with thumbscrews
- UL AWM rated for non-inwall use

**E-DB9F-F**

**Application:**

- Interconnection and Routing of RS-232 control
- Routing of non-TIA data using DE09 connections

**ECONOMY MOLDED D-SUB DB9 FEMALE TO FEMALE NULL MODEM CABLE**

Data & Control Cables

NON-PLENUM



**Features & Benefits:**

- D-SUB DE09 jack (female) to DE09 plug (male) connectors
- Null modem pin out
- Molded housings with thumbscrews
- UL AWM rated for non-inwall use

**E-DB9F-F-NULL**

**Application:**

- Interconnection and Routing of RS-232 control
- Null Modem format for control of remote devices
- Routing of non-TIA data using DE09 connections

**ECONOMY MOLDED D-SUB DB9 MALE TO FEMALE EXTENSION CABLE**

Data & Control Cables

NON-PLENUM



**Features & Benefits:**

- D-SUB DE09 jack (female) to DE09 plug (male) connectors
- Straight through pin out 1-1, 2-2, etc.
- Molded housings with thumbscrews
- UL AWM rated for non-inwall use

**E-DB9M-F**

**Application:**

- Interconnection and Routing of RS-232 control
- Extension of RS-232 cabling
- Routing of non-TIA data using DE09 connections

**ECONOMY MOLDED D-SUB DB9 MALE TO MALE RS-232 AND CONTROL CABLE**

Data & Control Cables

NON-PLENUM



FPO

**Features & Benefits:**

- D-SUB DE09 jack (female) to DE09 plug (male) connectors
- Straight through pin out 1-1, 2-2, etc.
- Molded housings with thumbscrews
- UL AWM rated for non-inwall use

**E-DB9M-M**

**Application:**

- Interconnection and Routing of RS-232 control
- Routing of non-TIA data using DE09 connections

**PLENUM RATED D-SUB RS-232 AND CONTROL CABLE**

Data & Control Cables

PLENUM

**FPO**



Features & Benefits:

- NA

**PDB9F-F**

Application:

- NA

**PLENUM RATED D-SUB DB9 FEMALE TO FEMALE NULL MODEM CABLE**

Data & Control Cables

PLENUM



Features & Benefits:

- NA

**PDB9F-F-NULL**

Application:

- NA

**PLENUM RATED D-SUB DB9 MALE TO FEMALE EXTENSION CABLE**

Data & Control Cables

PLENUM



Features & Benefits:

- NA

**PDB9M-F**

Application:

- NA

**PLENUM RATED D-SUB DB9 MALE TO MALE RS-232 AND CONTROL CABLE**

Data & Control Cables

PLENUM



Features & Benefits:

- NA

**PDB9M-M**

Application:

- NA



**HIGH RESOLUTION RCA MALE TO RCA MALE COMPOSITE VIDEO CABLE**

Digital Audio Cable

**COPPER CABLES**



**Features & Benefits:**

- RCA plug (male) to RCA plug (male) connectivity
- All gold plated contact surfaces
- Black metal connector body
- Serial digital dual shield RG59 size coaxial cable
- NEC CMR, CEC CMR FT4, RoHS Compliant
- Many lengths and custom on demand

**20SD-RCAM-M**


**Application:**

- Composite video patching, consumer device interconnect
- Line level unbalanced audio interconnection
- Inter and intra device A/V patching and routing
- S/PDIF coaxial audio

**HOSA TECHNOLOGY S/PDIF DIGITAL AUDIO RCA MALE TO RCA MALE CABLE**

Digital Audio Cable

**COPPER CABLES**



**Features & Benefits:**

- RCA male to RCA male Connectivity
- Metal shelled RCA plugs with gold contact surfaces
- RG59/U sized 75 Ohm coaxial cable construction
- OFC spiral shield for EMI rejection and flexibility
- Cable is blue in color
- Available in 1, 2, 3, 4, and 6 meter lengths

**DRA-500**

**Application:**

- S/PDIF Consumer digital coaxial audio interconnection
- Composite or Component Video interconnection
- Mono Analog Audio patching

**THX® CERTIFIED Z400 SERIES DIGITAL AUDIO S/PDIF RCA CABLE**

Digital Audio Cable

**COPPER CABLES**



**Features & Benefits:**

- NA

**Z400NDTHX**

**Application:**

- NA

**THX® CERTIFIED Z400 SERIES DIGITAL AUDIO S/PDIF RCA CABLE**

Digital Audio Cable

**COPPER CABLES**



**Features & Benefits:**

- Gold Plated RCA plugs with Glossy white enamel
- Orange banded for S/PDIF Digital Audio
- Silver Solder and Ohno-Continuous Cast Copper (OCC)
- Dual Shielded for low and high frequency use
- Polypropylene silk mesh overall jacket
- Available in 3.0 and 4.0 meters

**Z500NDTHX**

**Application:**

- S/PDIF Digital Audio, Composite Video
- Home Theater, High End Video

**PREMIUM METAL CONNECTOR TOSLINK DIGITAL OPTICAL AUDIO CABLE**

Digital Audio Cable  
OPTICAL CABLES



**Features & Benefits:**

- Metal EIAJ Optical Plug to Plug (TOSLINK) connectivity
- High Quality Polished End Face for low insertion loss
- 1mm Polymer Low Loss Optical Cable
- 2.2mm Polyethylene Cladding
- 4mm Polyvinyl Chloride Subjacket
- Flexible Polyvinyl Chloride dual layer Jacket
- Cable OD 7.5mm
- Satin Silver Jacket finish with White Connectors
- Retail Packaged

**Z500NTOS**

**Application:**

- Optical Digital Audio for consumer audio devices
- Device to Device interconnection of S/PDIF Digital audio

**ECONOMY MOLDED TOSLINK DIGITAL OPTICAL AUDIO CABLE**

Digital Audio Cable  
OPTICAL CABLES



**Features & Benefits:**

- EIAJ Optical Plug (Male) to EIAJ Optical Plug (Male)
- Molded Connector Housings
- Polymer 1mm Fiber Optic Core
- 655nm Wavelength, Attenuation less then 0.18 dB/m
- 25mm Bend Radius Minimum
- Flexible PVC Jacket
- Not UL listed, RoHS Compliant
- Standard lengths: 1, 2, 4, 6, 10 and 15 meters

**ZTOS**

**Application:**

- Digital Optical Audio Interconnection on Consumer devices
- Inter and Intra device interconnection of Digital Audio

**LIBERTY HDMI TO 19-PIN DIN DIGITAL MEDIA LEAD CABLE**

Digital EZ-Linx Cables  
NON-PLENUM



**Features & Benefits:**

- Modular Extension cable system for HDMI/DVI Signals
- DIN19 Male to HDMI "A" Male Connectivity
- This is the detachable 1/2 meter lead for the system
- Standard HDMI with Ethernet (2.25Gbps)
- Tested to 4.80 Gbps / 1080p60 / 150 MHz per TMDS
- Small Mold OD .630-inch / 16mm on DIN Molding
- In-wall rated CL2 and FT4, RoHS Compliant

**EZ-HDM**

**Application:**

- Routing HDMI or DVI through small conduit / holes
- European 20mm Molding for closed walls
- HDMI umbilical from Plate to Projector for non-plenum

**LIBERTY HDMI TO 19-PIN DIN DIGITAL MEDIA UMBILICAL CABLE**

Digital EZ-Linx Cables  
NON-PLENUM



**Features & Benefits:**

- Modular Extension cable system for HDMI/DVI Signals
- DIN19 Female to HDMI "A" Male Connectivity
- This is the longer umbilical component
- Standard HDMI with Ethernet (2.25Gbps)
- Tested to 4.80 Gbps / 1080p60 / 150 MHz per TMDS
- Small Mold OD .630-inch / 16mm on DIN Molding
- In-wall rated CL2 and FT4, RoHS Compliant

**EZ-HDM**

**Application:**

- Routing HDMI or DVI through small conduit / holes
- European 20mm Molding for closed walls
- HDMI umbilical from Plate to Projector for non-plenum

**LIBERTY PANEL MOUNT FEMALE HDMI 90 DEGREE TO 19-PIN DIN LEAD**

Digital EZ-Linx Cables  
NON-PLENUM



**Features & Benefits:**

- DIN19 Male to HDMI (A) Female 6-inches long
- 90 degree Female HDMI (A) Panel Mount
- Plate mountable
- UL rated CL2, CSA rated FT4
- HDMI Standard Speed supporting Ethernet and ARC

**EZV99M**

**Application:**

- EZ pull HDMI solutions through small molding and conduit
- Education and Boardroom HDMI applications
- Certified for in-wall use

CABLES | PRE-MADE & PATCH | DISPLAYPORT CABLES

**DISPLAYPORT TO HDMI MOLDED AWM RATED INTERCONNECTION CABLES**

DisplayPort Cables



**Features & Benefits:**

- 28 AWG Cabling
- Supports Resolutions to 3840x2160 to 6.5 feet
- Supports Resolutions to 2560x1600 to 15 feet
- Cable supports all HDMI out of DP resolutions
- Supports Audio and HDCP
- AWM Rated Cable for device interconnection
- Thumb activated locking latches on the DP plugs

**E-DPM-HDM**

**Application:**

- DisplayPort to HDMI Video/Audio adaption
- Inter and Intra device interconnection

**DISPLAYPORT MOLDED AWM RATED INTERCONNECTION CABLES**

DisplayPort Cables



**Features & Benefits:**

- 28 AWG Cabling
- Supports Resolutions to 3840x2160 to 6.5 feet
- Supports Resolutions to 2560x1600 to 15 feet
- Supports Audio and HDCP
- AWM Rated Cable for device interconnection
- Thumb activated locking latches on the DP plugs

**E-DPM-M**

**Application:**

- DisplayPort Video/Audio interconnection and routing
- Inter and Intra device interconnection

CABLES | PRE-MADE & PATCH | EDULINX | NON-PLENUM

**FLEX ADAPTER FOR FACEPLATE CONNECTION FOR SHARP BENDS**

EDULinx Cables  
NON-PLENUM



**Features & Benefits:**

- VGA with PC Audio. Not EDID Compatible.
- Composite Video RCA with L/R Audio RCA
- NOTE Audio Signals are Mono Only
- DIN 13 Single Connection on the back.

**EZ-ADAPTER-C1-0.5**

**Application:**

- NA

**LIBERTY EDULINX MODULAR INTERCONNECT SYSTEM MAIN UMBILICAL**

EDULinx Cables  
NON-PLENUM



**Features & Benefits:**

- DIN 13 female to female
- 26 AWG Stranded mini-High Resolution Coaxial cables
- This is the main umbilical
- Durable heavy duty molding and strain relief
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**EZ-LINX-C1**

**Application:**

- Single Pull Education, Boardroom installations
- Quick Installation component with matching faceplate
- Labor and Bill of Material Savings in mass installs

**LIBERTY EDULINX MODULAR INTERCONNECTION SYSTEM 2 VIDEO 2 AUDIO UMBILICAL**

EDULinx Cables  
NON-PLENUM



**Features & Benefits:**

- DIN 13 female to VGA+3.5TRS & triplex RCA audio/video
- 26 AWG Stranded mini-High Resolution Coaxial cables
- Mono Audio only, no stereo
- This is the umbilical attachment
- Durable heavy duty molding and strain relief
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**EZ-VGA3.53RCA**

**Application:**

- Single Pull Education, Boardroom installations
- Quick Installation component with matching faceplate
- Labor and Bill of Material Savings in mass installs

**LIBERTY EDULINX MODULAR INTERCONNECTION SYSTEM 2 VIDEO 2 AUDIO LEAD**

EDULinx Cables  
NON-PLENUM



**Features & Benefits:**

- VGA with PC Audio. Not EDID Compatible.
- Composite Video RCA with L/R Audio RCA
- NOTE Audio Signals are Mono Only
- DIN 13 Single Connection on the back.

**EZ-VGA3.53RCA-C1**

**Application:**

- NA

**LIBERTY EDULINX MODULAR INTERCONNECTION SYSTEM VGA WITH PC AUDIO MALE LEAD**

EDULinx Cables  
NON-PLENUM



**Features & Benefits:**

- DIN 13 male to VGA male and 3.5 TRS
- 26 AWG Stranded mini-High Resolution Coaxial cables
- Stereo PC Audio
- This is the lead attachment
- Durable heavy duty molding and strain relief
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**EZ-VGAMAM-C1**

**Application:**

- Single Pull Education, Boardroom installations
- Quick Installation component with matching faceplate
- Labor and Bill of Material Savings in mass installs

**LIBERTY PREMIUM MODULAR INTERCONNECTION SYSTEM 2 VIDEO 2 AUDIO PLENUM UMBILICAL**

EDULinx Cables  
PLENUM



**Features & Benefits:**

- DIN 13 female to VGA+3.5TRS & triplex RCA audio/video
- 26 AWG Stranded mini-High Resolution Coaxial cables
- Mono Audio only, no stereo
- This is the umbilical attachment
- Durable heavy duty metal construction
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**EZ-LINX-P-2V2A**

**Application:**

- Single Pull Education, Boardroom installations
- Quick Installation component with matching faceplate
- Labor and Bill of Material Savings in mass installs

**LIBERTY EZ-LINX 3 BNC MALE MODULAR INTERCONNECT SYSTEM LEAD**

EZ-LINX Cables  
NON-PLENUM



**Features & Benefits:**

- This is a 3 Video Leg for Component, Composite Video
- Male mini-mass DIN 13 to 3 RCA plug (male) connectors
- Threaded Coupling feature with locking ring
- OD over Mold is .710" / 18mm
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant
- EZ-LINX Attachment is nominally 1/2 meter (20 inches)


**EZ-3BNCM**

**Application:**

- Component Video, 3 Composite Video, Y/C Video
- Certified for In-Wall use

**LIBERTY EZ-LINX 3 RCA MALE MODULAR INTERCONNECT SYSTEM LEAD**

EZ-LINX Cables  
NON-PLENUM



**Features & Benefits:**

- This is a 3 Video Leg for Component, Composite Video
- Male mini-mass DIN 13 to 3 RCA plug (male) connectors
- Threaded Coupling feature with locking ring
- OD over Mold is .710" / 18mm
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant
- EZ-LINX Attachment is nominally 1/2 meter (20 inches)


**EZ-3RCAM**

**Application:**

- Component Video, 3 Composite Video, Y/C Video
- Certified for In-Wall use

**LIBERTY EZ-LINX 5 BNC MALE MODULAR INTERCONNECT SYSTEM LEAD**

EZ-LINX Cables  
NON-PLENUM



**Features & Benefits:**

- This is a 5 Video Leg for Component, Composite Video
- Male mini-mass DIN 13 to 5 RCA connectors
- Threaded Coupling feature with locking ring
- OD over Mold is .710" / 18mm
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant
- EZ-LINX Attachment is nominally 1/2 meter (20 inches)

**EZ-5BNCM**

**Application:**

- RGBHV Video, Component Video, Y/C, Composite Video
- Certified for In-Wall use

**LIBERTY EZ-LINX 5 BNC MALE WITH 3.5 AUDIO MODULAR INTERCONNECT SYSTEM LEAD**

EZ-LINX Cables  
NON-PLENUM



FPO

**Features & Benefits:**  
• NA

**EZ-5BNCMAM**

**Application:**  
• NA

**LIBERTY EZ-LINX 5 RCA FEMALE MODULAR INTERCONNECT SYSTEM LEAD**

EZ-LINX Cables  
NON-PLENUM



**Features & Benefits:**  
• This is a 5 video leg for component, composite video  
• Male mini-mass DIN 13 to 5 RCA jack (female) connectors  
• Threaded Coupling feature with locking ring  
• OD over Mold is .710" / 18mm  
• NEC CL2, CSA type AWM I/II A/B FT4, RoHS compliant  
• EZ-LINX Attachment is nominally 1/2 meter (20 inches)

**EZ-5RCAF**

**Application:**  
• RGBHV Video, Component Video, Y/C, Composite Video  
• Certified for In-Wall use

**LIBERTY EZ-LINX 5 RCA MALE MODULAR INTERCONNECT SYSTEM LEAD**

EZ-LINX Cables  
NON-PLENUM



**Features & Benefits:**  
• Attachment for ez-linx system. DIN 13 pin male with threaded collar to 5 rca plugs.

**EZ-5RCAM**

**Application:**  
• NA

**LIBERTY EZ-LINX 6 RCA MALE MODULAR INTERCONNECT SYSTEM LEAD**

EZ-LINX Cables  
NON-PLENUM



FPO

**Features & Benefits:**  
• NA

**EZ-6RCAM**

**Application:**  
• NA

**LIBERTY EZ-LINX FEMALE TO FEMALE 1' LINX CABLE**

EZ-LINX Cables



FPO

**Features & Benefits:**  
• This is the Umbilical Portion of the System  
• Female Mini-Mass DIN 13 Female on both ends  
• Threaded Coupling feature  
• Black molding on standard lengths, metal shell on others  
• OD over Mold is .710" / 18mm  
• NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant  
• This is the 1 foot coupler cable for short interconnects

**EZ-ADAPTER-F**

**Application:**  
• Analog Video, from composite video to RGBHV video  
• Establishing a Common infrastructure for various formats  
• Plate to display interconnection  
• Certified for in-wall use

**LIBERTY EZ-LINX MALE TO MALE 1' LINX CABLE**

**EZ-LINX Cables**  
**NON-PLENUM**



- Features & Benefits:**
- This is the Umbilical Portion of the System
  - Male Mini-Mass DIN 13 Female on both ends
  - Threaded Coupling feature
  - Black Molding on standard lengths, Metal shell on others
  - OD over Mold is .710" / 18mm
  - NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant
  - This is the 1 foot coupler cable for short interconnects

- EZ-ADAPTER-M**
- Application:**
- Analog Video, from Composite Video to RGBHV Video
  - Establishing a Common infrastructure for various formats
  - Plate to Display interconnection
  - Certified for In-Wall use

**LIBERTY EZ-LINX / EDULINX IN-LINE COUPLER**

**EZ-LINX Cables**  
**NON-PLENUM**



- Features & Benefits:**
- DIN 13 male to male in-line coupler
  - Black Molding, EZ-LINX and EDULINX compatible
  - Threaded couplings for high security

- EZ-BARREL-MM**
- Application:**
- Coupling two EZ-LINX or EDULINX umbilicals
  - Gender changing female DIN13 to male DIN13

**LIBERTY EZ-LINX DVI/A (ANALOG) MODULAR INTERCONNECT SYSTEM LEAD**

**EZ-LINX Cables**  
**NON-PLENUM**



- Features & Benefits:**
- DIN13 Male to DVI/A Analog Only Male Plug
  - This is the lead component of the Analog EZ-LINX system
  - DVI/A is VGA over DVI (RGBHV)
  - Designed for XGA (1024x768) support at 50 feet w/o AMPS
  - NEC CL2, CEC CMG FT4, RoHS Compliant

- EZ-DVI/A**
- Application:**
- PC Video from DVI/A or DVI-I PC System
  - In-wall rated for General Purpose ratings

**LIBERTY EZ-LINX MODULAR INTERCONNECT SYSTEM MAIN UMBILICAL**

**EZ-LINX Cables**  
**NON-PLENUM**



- Features & Benefits:**
- DIN 13 female to female
  - 26 AWG Stranded mini-High Resolution Coaxial cables
  - This is the main umbilical
  - Durable heavy duty molding and strain relief
  - NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

- EZ-LINX**
- Application:**
- Single Pull Education, Boardroom installations
  - Quick Installation component with matching faceplate
  - Labor and Bill of Material Savings in mass installs

**LIBERTY EZ-LINX / EDULINX PULLING CAP ATTACHMENT**

**EZ-LINX Cables**  
**NON-PLENUM**




- Features & Benefits:**
- Mating rotating cap for pulling EZ-LINX/EDULINX
  - Threads onto the female DIN13 jack
  - Pulling force up to 50 lbs (22 KG)
  - Durable heavy duty metal construction
  - Nose spins to prevent cable twisting

- EZ-LINX-CAP**
- Application:**
- Pulling EZ-LINX and EDULINX components
  - Labor saving and product protection during install

**LIBERTY EZ-LINX S-VIDEO AND 2 RCA MODULAR INTERCONNECT SYSTEM LEAD**

EZ-LINX Cables  
NON-PLENUM



**Features & Benefits:**

- This is an S-Video and Left/Right Audio leg
- Male Mini-Mass DIN 13 to SV Male and 2 RCA male
- Threaded Coupling feature with locking ring
- OD over Mold is .710" / 18mm
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant
- EZ-LINX Attachment is nominally 1/2 meter (20 inches)

**EZ-SVM-L/R**

**Application:**

- Y/C video and analog audio
- Certified for In-Wall use

**LIBERTY EZ-LINX S-VIDEO AND 3 RCA MODULAR INTERCONNECT SYSTEM LEAD**

EZ-LINX Cables  
NON-PLENUM



**Features & Benefits:**

- Custom ez-linx item

**EZ-SVM3RCAM**

**Application:**

- NA

**LIBERTY EZ-LINX MODULAR INTERCONNECT SYSTEM VGA MALE LEAD**

EZ-LINX Cables  
NON-PLENUM



**Features & Benefits:**

- This is a plug-n-play VGA (RGBHV) attachment
- Male mini-mass DIN 13 to DE15 jack (female) VGA connector
- Threaded Coupling feature with locking ring
- OD over Mold is .710" / 18mm
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant
- EZ-LINX Attachment is nominally 1/2 meter (20 inches)

**EZ-VGAF**

**Application:**

- RGBHV Video, Component Video
- Certified for In-Wall use

**LIBERTY EZ-LINX MODULAR INTERCONNECT SYSTEM VGA MALE LEAD**

EZ-LINX Cables  
NON-PLENUM



**Features & Benefits:**

- DIN 13 male to VGA male
- 26 AWG Stranded mini-High Resolution Coaxial cables
- ID/DDC compliant, does not support pin 9 EDID power
- This is the lead attachment
- Durable heavy duty molding and strain relief
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**EZ-VGAM**

**Application:**

- Single Pull Education, Boardroom installations
- Quick Installation component with matching faceplate
- Labor and Bill of Material Savings in mass installs



**LIBERTY DIGITAL EZ-LINX PULLING CAP**

EZ-LINX Pulling Tools



**Features & Benefits:**

- Pulling Cap with swivel feature
- Fits Digital EZ-LINX HDMI and DVI umbilicals
- 22Kg (50 lb) pull force
- Fits through 3/4" conduit or 20mm European molding

**EZ-DIN19-CAP**

**Application:**

- Pulling HDMI or DVI through small conduit / holes
- European 20mm Molding for closed walls

**LIBERTY EZ2-LINK/EZ-LINX PULLING CAP**

EZ-LINX Pulling Tools



**Features & Benefits:**

- Mating rotating cap for pulling EZ-LINX/EDULINX
- Threads onto the female DIN13 jack
- Pulling force up to 50 lbs (22 KG)
- Durable heavy duty metal construction
- Nose spins to prevent cable twisting

**EZ-LINX-CAP**

**Application:**

- Pulling EZ-LINX and EDULINX components
- Labor saving and product protection during install

**LIBERTY PREMIUM MODULAR INTERCONNECTION SYSTEM 2 VIDEO 2 AUDIO LEAD**

EZ2-LINK Cables  
NON-PLENUM



**Features & Benefits:**

- DIN 15 male to VGA+3.5TRS and Triplex RCA Audio/Video
- 26 AWG Stranded mini-High Resolution Coaxial cables
- Full Stereo Audio on both channels
- This is the lead attachment
- Durable heavy duty molding and strain relief
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**EZ2-2V2A**

**Application:**

- Single Pull Education, Boardroom installations
- Quick Installation component with matching faceplate
- Labor and Bill of Material Savings in mass installs

**LIBERTY PREMIUM MODULAR INTERCONNECTION SYSTEM 5 BNC MALE RGBHV MALE LEAD**

EZ2-LINK Cables  
NON-PLENUM



**Features & Benefits:**

- This is a 5 Video Leg for Component, Composite Video
- Male Mini-Mass DIN 15 to 5 BNC Plug (Male) Connectors
- Threaded Coupling feature with locking ring
- OD over Mold is .710" / 18mm
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant
- EZ-LINX Attachment is nominally 1 meter (40 inches)

**EZ2-5BM**

**Application:**

- RGBHV Video, Component Video, Y/C, Composite Video
- Certified for In-Wall use

**LIBERTY PREMIUM MODULAR INTERCONNECTION SYSTEM MAIN UMBILICAL FEMALE TO FEMALE**

EZ2-LINK Cables  
NON-PLENUM



**Features & Benefits:**

- This is the Umbilical Portion of the System
- Female Mini-Mass DIN 15 Female on both ends
- Threaded Coupling feature
- BLUE Molding on standard lengths
- OD over Mold is .710" / 18mm
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant
- Standard Lengths: 35,50 feet

**EZ2-FF**

**Application:**

- Analog Video, from Composite Video to RGBHV Video
- Establishing a Common infrastructure for various formats
- Plate to Display interconnection
- Certified for In-Wall use

**LIBERTY PREMIUM MODULAR INTERCONNECTION SYSTEM USER CONFIGURABLE MALE LEAD**

EZ2-LINK Cables  
NON-PLENUM



**Features & Benefits:**

- This is the user-configurable unterminated end
- Male Mini-Mass DIN 15 to Blunt end
- Threaded Coupling feature with locking ring
- OD over Mold is .710" / 18mm
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant
- EZ-LINX Attachment is nominally 6 feet long

**EZ2-TAIL**

**Application:**

- Component Video, 3 Composite Video, Y/C Video, RGBHV
- Analog Audio, S/PDIF Digital Audio
- Certified for In-Wall use

**LIBERTY PREMIUM MODULAR INTERCONNECTION SYSTEM VGA AND PC STEREO AUDIO LEAD**

EZ2-LINK Cables  
NON-PLENUM



**Features & Benefits:**

- DIN 15 male to VGA+3.5TRS Stereo Audio
- 26 AWG Stranded mini-High Resolution Coaxial cables
- Full Stereo Audio
- This is the lead attachment
- Durable heavy duty molding and strain relief
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant


**EZ2-VAM**

**Application:**

- Single Pull Education, Boardroom installations
- Quick Installation component with matching faceplate
- Labor and Bill of Material Savings in mass installs

**LIBERTY PREMIUM MODULAR INTERCONNECTION SYSTEM VGA AND PC STEREO AUDIO UMBILICAL**

E2Z-LINK Cables  
NON-PLENUM



**Features & Benefits:**

- Female Mini-Mass DIN 15 to VGA and 3.5 male
- Full Stereo Audio
- Threaded Coupling feature with locking ring
- OD over Mold is .710" / 18mm
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E2Z-VAM**

**Application:**

- Education and Boardroom VGA with audio applications
- RGBHV Video and PC Stereo Audio
- Certified for In-Wall use

**LIBERTY PREMIUM MODULAR INTERCONNECTION SYSTEM EDID COMPLIANT VGA FEMALE LEAD**

E2Z-LINK Cables  
NON-PLENUM



**Features & Benefits:**

- DIN 15 male to VGA female
- 26 AWG Stranded mini-High Resolution Coaxial cables
- Pin 9 EDID compliant
- This is the lead attachment
- Durable heavy duty molding and strain relief
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E2Z-VF**

**Application:**

- Single Pull Education, Boardroom installations
- Quick Installation component with matching faceplate
- Labor and Bill of Material Savings in mass installs

**LIBERTY PREMIUM MODULAR INTERCONNECTION SYSTEM EDID COMPLIANT VGA MALE LEAD**

E2Z-LINK Cables  
NON-PLENUM



**Features & Benefits:**

- DIN 15 male to VGA male
- 26 AWG Stranded mini-High Resolution Coaxial cables
- Pin 9 EDID compliant
- This is the lead attachment
- Durable heavy duty molding and strain relief
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E2Z-VM**

**Application:**

- Single Pull Education, Boardroom installations
- Quick Installation component with matching faceplate
- Labor and Bill of Material Savings in mass installs

**LIBERTY PREMIUM MODULAR INTERCONNECTION SYSTEM 2 VIDEO 2 AUDIO UMBILICAL**

EZ2-LINK Cables

PLENUM



**Features & Benefits:**

- DIN 15 female to VGA+3.5TRS and Triplex RCA Audio/ Video
- 26 AWG Stranded mini-High Resolution Coaxial cables
- Full Stereo Audio on both channels
- This is the umbilical attachment
- Durable heavy duty molding and strain relief
- NEC CL2P/CMP, CSA CMP FT6, RoHS Compliant

**EZ2-2V2A-P**

**Application:**

- Single Pull Education, Boardroom installations
- Quick Installation component with matching faceplate
- Labor and Bill of Material Savings in mass installs

**LIBERTY PREMIUM MODULAR INTERCONNECTION SYSTEM MAIN PLENUM RATED UMBILICAL**

EZ2-LINK Cables

PLENUM



**Features & Benefits:**

- DIN 15 female to female
- 26 AWG Stranded mini-High Resolution Coaxial cables
- This is the main umbilical
- Durable heavy duty molding and strain relief
- NEC CL2P/CMP, CSA CMP FT6, RoHS Compliant

**EZ2-FF-P**

**Application:**

- Single Pull Education, Boardroom installations
- Quick Installation component with matching faceplate
- Labor and Bill of Material Savings in mass installs

**LIBERTY PREMIUM MODULAR INTERCONNECTION SYSTEM VGA AND PC STEREO AUDIO UMBILICAL**

EZ2-LINK Cables

PLENUM



**Features & Benefits:**

- DIN 15 female to VGA+3.5TRS Stereo Audio
- 26 AWG Stranded mini-High Resolution Coaxial cables
- Full Stereo Audio
- This is the umbilical attachment
- Durable heavy duty molding and strain relief
- NEC CL2P/CMP, CSA CMP FT6, RoHS Compliant

**EZ2-VAM-P**

**Application:**

- Single Pull Education, Boardroom installations
- Quick Installation component with matching faceplate
- Labor and Bill of Material Savings in mass installs

**LIBERTY PREMIUM MODULAR INTERCONNECTION SYSTEM EDID COMPLIANT VGA MALE LEAD**

EZ2-LINK Cables

PLENUM



**Features & Benefits:**

- This is a full EDID compliant VGA (RGBHV) attachment
- Female Mini-Mass DIN 15 to DE15 Plug (Male) VGA Connector
- Threaded Coupling feature with locking ring
- OD over connector shell is .710" / 18mm
- NEC CMP, CEC CMP FT6, RoHS Compliant


**EZ2-VM-P**

**Application:**

- Education and Boardroom VGA and A/V applications
- Composite Video and RGBHV Video, 3.5 and L/R RCA Audio
- Certified for Plenum and in-wall use

**DUPLEX FIBER OPTIC PATCH CABLE OM1 STANDARD MULTIMODE LC-LC**

Fiber Optic Patch  
MULTIMODE OM1



- Features & Benefits:**
- OM1 62.5/125 Multimode Fiber
  - Zipcord style plenum rated construction
  - LC duplex to LC duplex Connectivity
  - 1, 2, 3 meters standard lengths, other lengths available on request
  - Orange colored jacket designates Standard Multimode
  - NEC OFNP, CEC FT6, RoHS compliant

**DMM6LCLC**

- Application:**
- 10/100/1000 Ethernet Fiber Patching
  - A/V, Data, Control, Phone Support
  - Economical solution to field termination
  - Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM1 STANDARD MULTIMODE LC-SC**

Fiber Optic Patch  
MULTIMODE OM1




- Features & Benefits:**
- OM1 62.5/125 Multimode Fiber
  - Zipcord style plenum rated construction
  - LC duplex to SC duplex Connectivity
  - 1, 2, 3 meters standard lengths, other lengths available on request
  - Orange colored jacket designates Standard Multimode
  - NEC OFNP, CEC FT6, RoHS compliant

**DMM6LCSC**

- Application:**
- 10/100/1000 Ethernet Fiber Patching
  - A/V, Data, Control, Phone Support
  - Economical solution to field termination
  - Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM1 STANDARD MULTIMODE LC-ST**

Fiber Optic Patch  
MULTIMODE OM1



- Features & Benefits:**
- OM1 62.5/125 Multimode Fiber
  - Zipcord style plenum rated construction
  - LC duplex to 2 x ST Connectivity
  - 1, 2, 3 meters standard lengths, other lengths available on request
  - Orange colored jacket designates Standard Multimode
  - NEC OFNP, CEC FT6, RoHS compliant

**DMM6LCST**

- Application:**
- 10/100/1000 Ethernet Fiber Patching
  - A/V, Data, Control, Phone Support
  - Economical solution to field termination
  - Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM1 STANDARD MULTIMODE SC-SC**

Fiber Optic Patch  
MULTIMODE OM1



- Features & Benefits:**
- OM1 62.5/125 Multimode Fiber
  - Zipcord style plenum rated construction
  - SC duplex to SC duplex Connectivity
  - 1, 2, 3 meters standard lengths, other lengths available on request
  - Orange colored jacket designates Standard Multimode
  - NEC OFNP, CEC FT6, RoHS compliant

**DMM6SCSC**

- Application:**
- 10/100/1000 Ethernet Fiber Patching
  - A/V, Data, Control, Phone Support
  - Economical solution to field termination
  - Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM1 STANDARD MULTIMODE SC-ST**

Fiber Optic Patch  
MULTIMODE OM1



- Features & Benefits:**
- OM1 62.5/125 Multimode Fiber
  - Zipcord style plenum rated construction
  - SC duplex to 2 x ST Connectivity
  - 1, 2, 3 meters standard lengths, other lengths available on request
  - Orange colored jacket designates Standard Multimode
  - NEC OFNP, CEC FT6, RoHS compliant

**DMM6SCST**

- Application:**
- 10/100/1000 Ethernet Fiber Patching
  - A/V, Data, Control, Phone Support
  - Economical solution to field termination
  - Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM1 STANDARD MULTIMODE ST-ST**

Fiber Optic Patch  
MULTIMODE OM1




- Features & Benefits:**
- OM1 62.5/125 Multimode Fiber
  - Zipcord style plenum rated construction
  - 2 x ST to 2 x ST Connectivity
  - 1, 2, 3 meters standard lengths, other lengths available on request
  - Orange colored jacket designates Standard Multimode
  - NEC OFNP, CEC FT6, RoHS compliant

- DMM6STST**
- Application:**
- 10/100/1000 Ethernet Fiber Patching
  - A/V, Data, Control, Phone Support
  - Economical solution to field termination
  - Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM2 STANDARD MULTIMODE LC-LC**

Fiber Optic Patch  
MULTIMODE OM2



- Features & Benefits:**
- OM2 50/125 Multimode Fiber
  - Zipcord style plenum rated construction
  - LC duplex to LC duplex Connectivity
  - 1, 2, 3 meters standard lengths, other lengths available on request
  - Orange colored jacket designates Standard Multimode
  - NEC OFNP, CEC FT6, RoHS compliant

- DMM5LCLC**
- Application:**
- 10/100/1000 Ethernet Fiber Patching
  - A/V, Data, Control, Phone Support
  - Economical solution to field termination
  - Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM2 STANDARD MULTIMODE LC-SC**

Fiber Optic Patch  
MULTIMODE OM2



- Features & Benefits:**
- OM2 50/125 Multimode Fiber
  - Zipcord style plenum rated construction
  - LC duplex to SC duplex Connectivity
  - 1, 2, 3 meters standard lengths, other lengths available on request
  - Orange colored jacket designates Standard Multimode
  - NEC OFNP, CEC FT6, RoHS compliant

- DMM5LCSC**
- Application:**
- 10/100/1000 Ethernet Fiber Patching
  - A/V, Data, Control, Phone Support
  - Economical solution to field termination
  - Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM2 STANDARD MULTIMODE LC-ST**

Fiber Optic Patch  
MULTIMODE OM2



- Features & Benefits:**
- OM2 50/125 Multimode Fiber
  - Zipcord style plenum rated construction
  - LC duplex to 2 x ST Connectivity
  - 1, 2, 3 meters standard lengths, other lengths available on request
  - Orange colored jacket designates Standard Multimode
  - NEC OFNP, CEC FT6, RoHS compliant

- DMM5LCST**
- Application:**
- 10/100/1000 Ethernet Fiber Patching
  - A/V, Data, Control, Phone Support
  - Economical solution to field termination
  - Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM2 STANDARD MULTIMODE SC-SC**

Fiber Optic Patch  
MULTIMODE OM2



- Features & Benefits:**
- OM2 50/125 Multimode Fiber
  - Zipcord style plenum rated construction
  - SC duplex to SC duplex Connectivity
  - 1, 2, 3 meters standard lengths, other lengths available on request
  - Orange colored jacket designates Standard Multimode
  - NEC OFNP, CEC FT6, RoHS compliant

**DMM5SCSC**

- Application:**
- 10/100/1000 Ethernet Fiber Patching
  - A/V, Data, Control, Phone Support
  - Economical solution to field termination
  - Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM2 STANDARD MULTIMODE SC-ST**

Fiber Optic Patch  
MULTIMODE OM2



- Features & Benefits:**
- OM2 50/125 Multimode Fiber
  - Zipcord style plenum rated construction
  - SC duplex to 2 x ST Connectivity
  - 1, 2, 3 meters standard lengths, other lengths available on request
  - Orange colored jacket designates Standard Multimode
  - NEC OFNP, CEC FT6, RoHS compliant

**DMM5SCST**

- Application:**
- 10/100/1000 Ethernet Fiber Patching
  - A/V, Data, Control, Phone Support
  - Economical solution to field termination
  - Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM2 STANDARD MULTIMODE ST-ST**

Fiber Optic Patch  
MULTIMODE OM2



- Features & Benefits:**
- OM2 50/125 Multimode Fiber
  - Zipcord style plenum rated construction
  - 2 x ST to 2 x ST Connectivity
  - 1, 2, 3 meters standard lengths, other lengths available on request
  - Orange colored jacket designates Standard Multimode
  - NEC OFNP, CEC FT6, RoHS compliant

**DMM5STST**

- Application:**
- 10/100/1000 Ethernet Fiber Patching
  - A/V, Data, Control, Phone Support
  - Economical solution to field termination
  - Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM3 LASER OPTIMIZED MULTIMODE LC-LC**

Fiber Optic Patch  
MULTIMODE OM3



- Features & Benefits:**
- OM3 50/125 Laser Optimized Multimode Fiber
  - Zipcord style plenum rated construction
  - LC duplex to LC duplex Connectivity
  - 1, 2, 3 meters standard lengths, other lengths available on request
  - Aqua colored jacket designates Laser Optimized Multimode
  - NEC OFNP, CEC FT6, RoHS compliant

**DMM10LCLC**

- Application:**
- 10/100/1000/10G Ethernet Fiber Patching
  - Crestron, AMX, Savant system support
  - Economical solution to field termination
  - Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM3 LASER OPTIMIZED MULTIMODE LC-SC**

Fiber Optic Patch

MULTIMODE OM3



**Features & Benefits:**

- OM3 50/125 Laser Optimized Multimode Fiber
- Zipcord style plenum rated construction
- LC duplex to SC duplex Connectivity
- 1, 2, 3 meters standard lengths, other lengths available on request
- Aqua colored jacket designates Laser Optimized Multimode
- NEC OFNP, CEC FT6, RoHS compliant

**DMM10LCSC**

**Application:**

- 10/100/1000/10G Ethernet Fiber Patching
- Crestron, AMX, Savant system support
- Economical solution to field termination
- Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM3 LASER OPTIMIZED MULTIMODE LC-ST**

Fiber Optic Patch

MULTIMODE OM3



**Features & Benefits:**

- OM3 50/125 Laser Optimized Multimode Fiber
- Zipcord style plenum rated construction
- LC duplex to 2 x ST Connectivity
- 1, 2, 3 meters standard lengths, other lengths available on request
- Aqua colored jacket designates Laser Optimized Multimode
- NEC OFNP, CEC FT6, RoHS compliant

**DMM10LCST**

**Application:**

- 10/100/1000/10G Ethernet Fiber Patching
- Crestron, AMX, Savant system support
- Economical solution to field termination
- Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM3 LASER OPTIMIZED MULTIMODE SC-SC**

Fiber Optic Patch

MULTIMODE OM3



**Features & Benefits:**

- OM3 50/125 Laser Optimized Multimode Fiber
- Zipcord style plenum rated construction
- SC duplex to SC duplex Connectivity
- 1, 2, 3 meters standard lengths, other lengths available on request
- Aqua colored jacket designates Laser Optimized Multimode
- NEC OFNP, CEC FT6, RoHS compliant

**DMM10SCSC**

**Application:**

- 10/100/1000/10G Ethernet Fiber Patching
- Crestron, AMX, Savant system support
- Economical solution to field termination
- Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM3 LASER OPTIMIZED MULTIMODE SC-ST**

Fiber Optic Patch

MULTIMODE OM3



**Features & Benefits:**

- OM3 50/125 Laser Optimized Multimode Fiber
- Zipcord style plenum rated construction
- SC duplex to 2 x ST Connectivity
- 1, 2, 3 meters standard lengths, other lengths available on request
- Aqua colored jacket designates Laser Optimized Multimode
- NEC OFNP, CEC FT6, RoHS compliant

**DMM10STSC**

**Application:**

- 10/100/1000/10G Ethernet Fiber Patching
- Crestron, AMX, Savant system support
- Economical solution to field termination
- Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OM3 LASER OPTIMIZED MULTIMODE ST-ST**

Fiber Optic Patch

MULTIMODE OM3



**Features & Benefits:**

- OM3 50/125 Laser Optimized Multimode Fiber
- Zipcord style plenum rated construction
- 2 x ST to 2 x ST Connectivity
- 1, 2, 3 meters standard lengths, other lengths available on request
- Aqua colored jacket designates Laser Optimized Multimode
- NEC OFNP, CEC FT6, RoHS compliant

**DMM10STST**

**Application:**

- 10/100/1000/10G Ethernet Fiber Patching
- Crestron, AMX, Savant system support
- Economical solution to field termination
- Always patch out to equipment! It is the standard



**STRONGER, SAFER, FASTER (SSF) LIFETIME FIBER OPTIC PATCH CABLE OM3 LASER OPTIMIZED MULTIMODE LC-LC**

Fiber Optic Patch  
**MULTIMODE SSF OM3**



- Features & Benefits:**
- Duplex LC to Duplex LC FPC/SPC Format Connectors
  - Stronger, Safer, Faster (SSF) fiber bulk cable
  - 10,000 times the flex life of standard fiber cables
  - 2 Fiber 50/125 Laser Optimized Multimode OM3 Fiber
  - Standard lengths 1, 2, 3, 5, and 10 meters
  - NEC OFNR, CEC FT4, RoHS Compliant

- DOM3NLCCLC**
- Application:**
- Super strong long life duplex fiber patch cables
  - LAN 10/100/1000/10G Ethernet
  - Digital Multimedia patching and interconnection
  - Crestron, AMX, and Savant standard fiber specification

**STRONGER, SAFER, FASTER (SSF) LIFETIME FIBER OPTIC PATCH CABLE OM3 LASER OPTIMIZED MULTIMODE LC-SC**

Fiber Optic Patch  
**MULTIMODE SSF OM3**



- Features & Benefits:**
- Duplex LC to Duplex LC FPC/SPC Format Connectors
  - Stronger, Safer, Faster (SSF) fiber bulk cable
  - 10,000 times the flex life of standard fiber cables
  - 2 Fiber 50/125 Laser Optimized Multimode OM3 Fiber
  - Standard lengths 1, 2, 3, 5, and 10 meters
  - NEC OFNR, CEC FT4, RoHS Compliant

- DOM3NLCSC**
- Application:**
- Super strong long life duplex fiber patch cables
  - LAN 10/100/1000/10G Ethernet
  - Digital Multimedia patching and interconnection
  - Crestron, AMX, and Savant standard fiber specification

**STRONGER, SAFER, FASTER (SSF) LIFETIME FIBER OPTIC PATCH CABLE OM3 LASER OPTIMIZED MULTIMODE SC-SC**

Fiber Optic Patch  
**MULTIMODE SSF OM3**




- Features & Benefits:**
- Duplex SC to Duplex SC FPC/SPC Format Connectors
  - Stronger, Safer, Faster (SSF) fiber bulk cable
  - 10,000 times the flex life of standard fiber cables
  - 2 Fiber 50/125 Laser Optimized Multimode OM3 Fiber
  - Standard lengths 1, 2, 3, 5, and 10 meters
  - NEC OFNR, CEC FT4, RoHS Compliant

- DOM3NSCSC**
- Application:**
- Super strong long life duplex fiber patch cables
  - LAN 10/100/1000/10G Ethernet
  - Digital Multimedia patching and interconnection
  - Crestron, AMX, and Savant standard fiber specification

**DUPLEX FIBER OPTIC PATCH CABLE OS1 SINGLE MODE LC-LC**

Fiber Optic Patch  
**SINGLE MODE**



- Features & Benefits:**
- OS1 9/125 Single Mode Fiber
  - Zipcord style plenum rated construction
  - LC duplex to LC duplex Connectivity
  - 1, 2, 3 meters standard lengths, other lengths available on request
  - Yellow colored jacket designates Single Mode
  - NEC OFNP, CEC FT6, RoHS compliant

- DSMLCLC**
- Application:**
- 10/100/1000/10G/40G/100G Ethernet Fiber Patching
  - A/V, Data, Control, Phone Support
  - TELCO, HD Security, High Bandwidth Signals
  - Economical solution to field termination
  - Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OS1 SINGLE MODE LC-SC**

Fiber Optic Patch  
**SINGLE MODE**



- Features & Benefits:**
- Duplex Zip Cord 2-Fiber Patch Cable
  - Duplex LC to Duplex SC connectivity
  - UPC end face format
  - Single mode 9/125 fiber
  - Cable is OFNR / FT4 rated
  - Yellow color indicates Single mode Fiber

- DSMLCSC**
- Application:**
- Fiber Patching in racks, enclosures and to devices
  - Networking, HD Video, Security Video
  - Note: APC end face required for CATV or Satellite Video

**DUPLEX FIBER OPTIC PATCH CABLE OS1 SINGLE MODE LC-ST**

Fiber Optic Patch  
**SINGLE MODE**




- Features & Benefits:**
- OS1 9/125 Single Mode Fiber
  - Zipcord style plenum rated construction
  - LC duplex to 2 x ST Connectivity
  - 1, 2, 3 meters standard lengths, other lengths available on request
  - Yellow colored jacket designates Single Mode
  - NEC OFNP, CEC FT6, RoHS compliant

- DSMLCST**
- Application:**
- 10/100/1000/10G/40G/100G Ethernet Fiber Patching
  - A/V, Data, Control, Phone Support
  - TELCO, HD Security, High Bandwidth Signals
  - Economical solution to field termination
  - Always patch out to equipment! It is the standard

**DUPLEX FIBER OPTIC PATCH CABLE OS1 SINGLE MODE SC-SC**

Fiber Optic Patch  
**SINGLE MODE**



- Features & Benefits:**
- Duplex Zip Cord 2-Fiber Patch Cable
  - Duplex SC to Duplex SC connectivity
  - UPC end face format
  - Single mode 9/125 fiber
  - Cable is OFNR / FT4 rated
  - Yellow color indicates Single mode Fiber

- DSMSCSC**
- Application:**
- Fiber Patching in racks, enclosures and to devices
  - Networking, HD Video, Security Video
  - Note: APC end face required for CATV or Satellite Video

**DUPLEX FIBER OPTIC PATCH CABLE OS1 SINGLE MODE SC-ST**

Fiber Optic Patch  
**SINGLE MODE**



- Features & Benefits:**
- Duplex Zip Cord 2-Fiber Patch Cable
  - Duplex SC to two ST connectivity
  - UPC end face format
  - Single mode 9/125 fiber
  - Cable is OFNR / FT4 rated
  - Yellow color indicates Single mode Fiber

- DSMSCST**
- Application:**
- Fiber Patching in racks, enclosures and to devices
  - Networking, HD Video, Security Video
  - Note: APC end face required for CATV or Satellite Video

**DUPLEX FIBER OPTIC PATCH CABLE OS1 SINGLE MODE ST-ST**

Fiber Optic Patch  
**SINGLE MODE**



- Features & Benefits:**
- Duplex Zip Cord 2-Fiber Patch Cable
  - Two ST to two ST connectivity
  - UPC end face format
  - Single mode 9/125 fiber
  - Cable is OFNR / FT4 rated
  - Yellow color indicates Single mode Fiber

- DSMSTST**
- Application:**
- Fiber Patching in racks, enclosures and to devices
  - Networking, HD Video, Security Video
  - Note: APC end face required for CATV or Satellite Video

**USB POWER SUPPLY FOR DFO-\* CABLES, 1A**

HDMI Cables  
ACCESSORIES



- Features & Benefits:**
- USB power adapter
  - Input: AC 100V-240V
  - Output: 5Vdc - 900ma-1000ma
  - White

**42-AC-2**

- Application:**
- USB Power source for Celerity, USB powered devices
  - Cell Phone, iPad charging

**CELERITY DFO SERIES HDMI RECEIVER CONNECTOR**

HDMI Cables  
ACCESSORIES



- Features & Benefits:**
- Detachable HDMI Receive unit
  - USB cable connection for power
  - 21.0 Gbps data rate for HDMI 2.0 4K@60Hz

**DFO-RX**

- Application:**
- Replacement Receiver end of the DFO series
  - Repair and troubleshooting tool

**CELERITY DFO SERIES HDMI RECEIVER CONNECTOR**

HDMI Cables  
ACCESSORIES



- Features & Benefits:**
- Detachable HDMI Transmit unit
  - USB cable connection for power
  - 21.0 Gbps data rate for HDMI 2.0 4K@60Hz

**DFO-TX**

- Application:**
- Replacement Transmitter end of the DFO series
  - Repair and troubleshooting tool

**LIBERTY PREMIUM HOME THEATER HIGH RETENTION HIGH SPEED HDMI® WITH ETHERNET CABLES**

HDMI Cables  
NON-PLENUM



- Features & Benefits:**
- High retention gold plated HDMI "A" plugs
  - EMI resistant can under the molding
  - Super flexible UL listed PVC jacketing
  - Up to 2 meters rated for 18.0 Gbps
  - 3 to 10 meters rated for 10.2 Gbps
  - 5 meter and greater are Active and Directional!
  - 4K video, Audio Return, Ethernet, CEC
  - NEC CL2, CEC CMG FT4, RoHS/REACH Compliant

**D2-HDSEM-M**

- Application:**
- Residential and Home Theater HDMI connectivity
  - 3D, 4K, Deep Color applications and installations
  - Audio/Visual equipment hookup and much more

**DIGITALINX HOME THEATER GRADE HIGH SPEED HDMI CABLE**

HDMI Cables  
NON-PLENUM



- Features & Benefits:**
- Gold Plated Contact Surfaces
  - Full Metal Hoods
  - 28 AWG triple shielded cable
  - Aesthetically pleasing polypro mesh netting -black/violet
  - High Speed HDMI ATC certified product
  - 4Kx2K, 3D, Deep Color, All Audio formats, CEC
  - Retail packaging - Bundt Cake type insert/box

**DLX-HDSM**

- Application:**
- HDMI Audio and Video Digital Media transmission
  - Home Theater Grade Product

**LIBERTY PREMIUM MOLDED HDMI TO DVI DIGITAL CABLE**

HDMI Cables  
NON-PLENUM



- Features & Benefits:**
- HDMI "A" Male to DVI-D Male Single Link Connectivity
  - 28 AWG TMDS Pair Construction
  - Triple Shielded Cable Construction
  - Reduced DVI molding for high density bays
  - NEC CL2 and CEC FT4 for In-wall use, RoHS Compliant
  - DVI 1.0 5.0 Gbps / 1900x1200 WUXGA / 1080p60

**E-HDM-DVI**

- Application:**
- Interconnection of HDMI Video to DVI Sinks (Displays)
  - Interconnection of DVI Video to HDMI Sinks (Displays)
  - In-wall listed per UL444, UL13 and the NEC

**LIBERTY HIGH SPEED HDMI WITH ETHERNET CABLE**

HDMI Cables  
NON-PLENUM



- Features & Benefits:**
- HDMI "A" Male to "A" Male Connectivity
  - All Gold Plated Contact Surfaces
  - 24 AWG TMDS Pair Construction
  - Active equalization and boost circuitry built in
  - Not directional
  - NEC CL2, CSA CMG FT4, RoHS Compliant
  - Third Party ATC Certified HDMI High Speed with Ethernet
  - 10.2 Gbps / 4Kx2K / 3D / Audio Return / CEC / Ethernet

**E-HDSEM-M**

- Application:**
- HDMI Digital Multimedia Device Interconnection
  - HDMI Device to wall and in-wall Interconnection
  - Inter and Intra device Interconnection

**TABLETOP HDMI, VGA AND AUDIO HYBRID CABLES**

HDMI Cables  
NON-PLENUM



- Features & Benefits:**
- Digital HDMI and Analog VGA plus Audio in one cable
  - Siamese or SPT type cabling format
  - 28 AWG HDMI for superior bandwidth and headroom
  - 32 AWG coaxial VGA for WUXGA to 19 feet
  - UL and CSA listed product, AWM for non in-wall use
  - 10.2 Gbps / 4Kx2K / 3D / Audio Return / CEC / Ethernet

**E-HDVAM-M**

- Application:**
- Tabletop or podium mobile device connection
  - Presentation systems and boardroom A/V connectivity
  - Inter and Intra device Interconnection

**LIBERTY MICRO HIGH SPEED HDMI CABLE**

HDMI Cables  
NON-PLENUM



- Features & Benefits:**
- HDMI "A" Male to "A" Male Connectivity
  - Ultra small flexible diameter cable 3.6mm in diameter
  - Flexible Polyvinyl Chloride Jacket
  - AWM rated, RoHS Compliant
  - ATC Certified HDMI(R) High Speed with Ethernet
  - 10.2 Gbps / 4Kx2K / 3D / CEC
  - Lengths 2m and longer are directional
  - 4m length does not support Ethernet

**E-MHDM-M**

- Application:**
- HDMI Digital Multimedia Device Interconnection
  - Direct rack patching HDMI equipment
  - Inter and Intra device Interconnection

**LIBERTY COMMERCIAL GRADE HIGH RETENTION HIGH SPEED HDMI WITH ETHERNET CABLE**

HDMI Cables  
NON-PLENUM



- Features & Benefits:**
- High retention gold plated HDMI "A" plugs
  - fully shielded from connector shroud to shroud
  - All lengths rated for 10.2 Gbps
  - 5 meters and longer are active and directional
  - 4K video, Audio Return, Ethernet, CEC
  - NEC CL2, CEC CMG FT4, RoHS/REACH Compliant

**E2-HDSEM-M**

- Application:**
- Commercial and Residential HDMI connectivity
  - 3D, 4K, Deep Color applications and installations
  - Audio/Visual equipment hookup and much more

**PERFECT PATH'S LOCKING HIGH SPEED HDMI WITH ETHERNET CABLE**

HDMI Cables  
NON-PLENUM



- Features & Benefits:**
- HDMI "A" Male to "A" Male Connectivity
  - All Gold Plated Contact Surfaces
  - 25Lb retention patented locking connector technology
  - 28 AWG TMDS pairs
  - Built in equalizer/booster circuit on lengths 16' & longer
  - FR-PVC, Flame Rated Flexible Polyvinyl Chloride Jacket
  - NEC CL2, CSA CMG FT4, RoHS Compliant
  - Third Party ATC Certified HDMI High Speed with Ethernet
  - 10.2 Gbps / 4Kx2K / 3D / Audio Return / CEC / Ethernet
  - All HDMI Audio formats supported

**HD-1000**

- Application:**
- HDMI digital multimedia integration & interconnection
  - Home theater HDMI connection
  - Inter and Intra device HDMI interconnection.

**PERFECT PATH'S HIGH RETENTION HIGH SPEED HDMI WITH AUDIO RETURN CABLE**

HDMI Cables  
NON-PLENUM



- Features & Benefits:**
- HDMI "A" Male to "A" Male Connectivity
  - All Gold Plated Contact Surfaces
  - 12Lb retention patented locking connector technology
  - 28 AWG TMDS pairs
  - FR-PVC, Flame Rated Flexible Polyvinyl Chloride Jacket
  - NEC CL2, CSA CMG FT4, RoHS Compliant
  - Third Party ATC Certified HDMI High Speed
  - 10.2 Gbps / 4Kx2K / 3D / Audio Return / CEC
  - All HDMI Audio formats supported

**HD-600**

- Application:**
- HDMI digital multimedia integration and interconnection
  - Home theater HDMI connection
  - Inter and Intra device HDMI interconnection

**PERFECT PATH'S LOCKING HIGH SPEED HDMI WITH AUDIO RETURN CABLE**

HDMI Cables  
NON-PLENUM




- Features & Benefits:**
- HDMI "A" Male to "A" Male Connectivity
  - All Gold Plated Contact Surfaces
  - 25Lb retention patented locking connector technology
  - 28 AWG TMDS pairs
  - Built in equalizer/booster circuit
  - FR-PVC, Flame Rated Flexible Polyvinyl Chloride Jacket
  - NEC CL2, CSA CMG FT4, RoHS Compliant
  - Third Party ATC Certified HDMI High Speed
  - 10.2 Gbps / 4Kx2K / 3D / Audio Return / CEC
  - All HDMI Audio formats supported

**HD-700**

- Application:**
- HDMI digital multimedia integration & interconnection
  - Home theater HDMI connection
  - Inter and Intra device HDMI interconnection

**LIBERTY REDUCED PROFILE HDMI PATCHING CABLES WITH HIGH RETENTION**

HDMI Cables  
NON-PLENUM



- Features & Benefits:**
- High retention gold plated HDMI "A" plugs
  - fully shielded from connector shroud to shroud
  - Up to 8 feet rated 10.2Gbps, up to 15 feet 5.0 Gbps
  - Up to 8 feet supports 4K, up to 15' supports 1080p60
  - Audio Return, Ethernet, CEC on all lengths
  - AWM rated, RoHS/REACH Compliant

**M2-HDSEM-M**

- Application:**
- HDMI patching, rack HDMI management and routing
  - Low profile required HDMI connectivity solutions
  - Audio/Visual equipment hookup and much more

**ECONOMY HIGH SPEED HDMI CABLE**

HDMI Cables  
NON-PLENUM



- Features & Benefits:**
- Economy construction
  - HDMI "A" Male to "A" Male Connectivity
  - Black molding and cable
  - 28 AWG TMDS Pair Construction
  - Dual Layer Foil and High % Braid shielding
  - FR-PVC, Flame Rated Flexible Polyvinyl Chloride Jacket
  - AWM rated, RoHS Compliant
  - Third Party ATC Certified HDMI(R) High Speed
  - 10.2 Gbps / 4Kx2K / 3D / CEC / ARC
  - All HDMI audio formats supported, audio return supported

**Z100HD**

- Application:**
- HDMI Digital Multimedia Device Interconnection
  - Rack patching HDMI equipment
  - Inter and Intra device Interconnection

**ECONOMY HIGH SPEED HDMI WITH ETHERNET CABLE**

**HDMI Cables**

**NON-PLENUM**



**Features & Benefits:**

- HDMI "A" Male to "A" Male Connectivity
- Black molding and cable
- 28 AWG TMDs Pair Construction
- Dual Layer Foil and High % Braid shielding
- Flexible Polyvinyl Chloride Jacket
- High Speed HDMI(R) with Ethernet rated
- 10.2 Gbps / 4K Video / 3D / CEC / ARC
- UL listed and AWM rated, RoHS Compliant

**Z100HDE**

**Application:**

- HDMI Digital Multimedia Device Interconnection
- Rack patching HDMI equipment
- Inter and Intra device Interconnection

**CELERITY PLENUM RATED FIBER OPTIC HDMI LONG DISTANCE CABLE**

**HDMI Cables**

**PLENUM**



**Features & Benefits:**

- Plenum rated cable for all installations
- Ultra-Small diameter cable
- Detachable HDMI TX and RX units from main body
- USB Power A plug on both TX and RX units
- TX end only needs USB power if the LED does not illuminate
- Lengths: 35, 40, 50, 60, 80, 100, 160, 200, 500, 1000 ft
- HDMI High Speed, 10.2Gbps, 4Kx2K, 3D, all Audio formats

**DFO**

**Application:**

- HDMI Projectors, Displays in commercial and residential
- Maximum bandwidth and distance needs for HDMI installs

**LIBERTY PLENUM RATED HYBRID COPPER / FIBER OPTIC HDMI LONG DISTANCE CABLE**

**HDMI Cables**

**PLENUM**



**Features & Benefits:**

- Plenum rated cable for all installations
- Ultra-Small diameter cable
- No additional power required
- Hybrid Copper/Fiber supports Hot Plug Detect
- Lengths: 10,15,20,23,30,40,50,60,70,80,90, and 100m
- HDMI High Speed, 6.75Gbps, 1080P, 3D, all Audio formats
- Does not support Ethernet or Audio Return

**DL-AOCHP**

**Application:**

- HDMI Projectors, Displays in commercial and residential
- Long distance cabling used with switches and DA's
- Digital Signage applications

**PLENUM RATED HD CABLE WITH ACTIVE DIRECTIONAL CHIPSETS**

**HDMI Cables**

**PLENUM**



**Features & Benefits:**

- 24 AWG Construction for low loss / zero bit error signals
- Black Molding
- CMP 75C Plenum rated for the US and Canada
- Gold Plated contacts
- Active Equalizer and Booster built into the cable
- NOTE: This Cable is Directional! See Instructions!
- 10.2 Gbps / 4Kx2K Video / All Audio formats
- Non-ATC certified as CEC is not supported

**P-HDM-M (HD)**

**Application:**

- HDMI digital multimedia in NEC plenum regulated installs
- DVI Digital Video in NEC Plenum regulated installs
- Backwards Compatible to all non-Plenum NEC applications

**PLENUM RATED HIGH SPEED HDMI WITH ETHERNET CABLE**

HDMI Cables  
**PLENUM**



**Features & Benefits:**

- 24 AWG Construction for low loss / zero bit error signals
- Black Molding
- CMP 75C Plenum rated for the US & Canada
- Gold Plated contacts
- ATC certified to 10.2 Gbps / 4K x 2K & all audio formats
- Supports CEC, audio return channel (ARC), Ethernet

**P-HDM-M (HS)**

**Application:**

- HDMI digital multimedia in NEC plenum regulated installs
- DVI Digital Video in NEC Plenum regulated installs
- Backwards Compatible to all non-Plenum NEC applications

**PLENUM RATED STANDARD HDMI WITH ETHERNET CABLE**

HDMI Cables  
**PLENUM**



**Features & Benefits:**

- 24 AWG Construction for low loss / zero bit error signals
- Black Molding
- CMP 75C Plenum rated for the US and Canada
- Gold Plated contacts
- ATC certified to 2.25 Gbps / 1080p24 & all audio formats
- Supports Audio Return Channel (ARC), Ethernet

**P-HDM-M (SS)**

**Application:**

- HDMI digital multimedia in NEC plenum regulated installs
- DVI Digital Video in NEC Plenum regulated installs
- Backwards Compatible to all non-Plenum NEC applications

**ATLAS SOUND TACTICAL MICROPHONE AND BALANCED AUDIO XLR CABLES**

Microphone Cables  
**NON-PLENUM**



**Features & Benefits:**

- XLR 3-Pin Plug (Male) to XLR 3-Pin Jack (Female)
- Custom molded Sure Grip Connectors
- Oxygen free copper conductors
- Class II shielding and a PolyFlex outer jacket

**AS2XLR-**

**Application:**

- Microphone level audio, Line Level MONO Balanced Audio
- Line Level Stereo Unbalanced Audio
- Device interconnection of audio systems

**HOSA EDGE XLR MICROPHONE CABLES**

Microphone Cables  
**NON-PLENUM**



**Features & Benefits:**

- Original Neutrik connectors for security and durability
- 20 AWG Oxygen-Free Copper for maximum signal transfer
- Low capacitance for crystal-clear highs and lows
- Durable and designed for stage and tactical use
- Available in 3,5,10,15,20,25,30,50,75 and 100 feet

**CMK-**

**Application:**

- Microphone level audio, Line Level MONO Balanced Audio
- Line Level Stereo Unbalanced Audio
- Tactical and high movement Audio and Mic patching

**HOSA TECHNOLOGY PRO MICROPHONE XLR 3-PIN MALE TO FEMALE CABLES**

Microphone Cables  
NON-PLENUM



**Features & Benefits:**

- XLR 3-pin male to XLR 3-pin female connectivity
- Silver-plated REAN connectors for superior signal transfer
- 20 AWG Oxygen-Free Copper for a louder, clearer signal
- 90% OFC braided shield for a higher signal to noise ratio
- Balanced format
- Available lengths: 3,5,10,15,20,25,30,50, and 100 feet

**HMIC-**

**Application:**

- Microphone level audio, Line Level MONO Balanced Audio
- Line Level Stereo Unbalanced Audio
- Tactical and high movement Audio and Mic patching

**LIBERTY TACTICAL MICROPHONE AND AUDIO XLR 3-PIN MALE TO FEMALE CABLE**

Microphone Cables  
NON-PLENUM



**Features & Benefits:**

- Neutrik brand pro audio XLR connectors
- XLR 3-Pin Plug (Male) to XLR 3-Pin Jack (Female)
- Silver solder lead free and RoHS compliant
- X-Cross 2 Pair twisted, shielded pair base cable
- 95% Tinned Copper Braid Shield for EMI rejection
- NEC CM, CEC CMG FT4, RoHS Compliant
- Any length available on request, built to order

**SQ-XLRM-F**

**Application:**

- Microphone level audio, Line Level MONO Balanced Audio
- Line Level Stereo Unbalanced Audio
- Tactical and high movement Audio and Mic patching

**LIBERTY PLENUM RATED AUDIO / MICROPHONE XLR 3-PIN MALE TO FEMALE CABLES**

Microphone Cables  
PLENUM



**Features & Benefits:**

- NA

**P221P-XLRM-F**

**Application:**

- NA



**TRIPPLITE PREMIUM UL LISTED IEC 60320 C13 TO IEC 60320 C14 18 AWG 10 AMP POWER CORDS****Power Extension Cords****CPU'S & DISPLAYS****Features & Benefits:**

- Male to female power extension cord for PC/device
- Plug type: IEC-320-C14 (male) to IEC-320-C13 (female)
- Cable 18 AWG SJT, 10A, 100-250V
- UL Listed

**P004****Application:**

- Power cord extension for a PC or other C13 device
- Directly connect device to a PDU or UPS

**TRIPPLITE PREMIUM UL LISTED IEC 60320 C13 TO IEC 60320 C14 14 AWG 15 AMP POWER CORDS****Power Extension Cords****CPU'S & DISPLAYS****Features & Benefits:**

- Molded, Heavy-Duty Power Cable, 10 ft.
- IEC-60320-C13 to IEC-60320-C14
- 14 AWG x 3C, SJT, 15A, 100-250 Volt
- RoHS Compliant
- UL Listed

**P005****Application:**

- Ideal for home or office solutions
- Extend power cables for efficiency of office layouts

**ECONOMY UL LISTED IEC 60320 C13 TO IEC 60320 C14 18 AWG 10 AMP POWER CORDS****Power Extension Cords****CPU'S & DISPLAYS****Features & Benefits:**

- Standard Computer Power Cord rated for 10A
- Power Extension cable for a PC printer or monitor
- Plug Type - IEC-320-C13 to IEC-320-C14
- Universal design
- 18 AWG SJT rated cable
- In 3, 6, and 12 foot lengths

**P10A-C13-C14****Application:**

- Extend C13 power cables
- Rack cord management and cord cleanup

**ECONOMY UL LISTED IEC 60320 C13 TO IEC 60320 C14 16 AWG 13 AMP POWER CORDS****Power Extension Cords****CPU'S & DISPLAYS****Features & Benefits:**

- Standard Computer Power Cord rated for 13A
- Power Extension cable for a PC printer or monitor
- Plug Type - IEC-320-C13 to IEC-320-C14
- Universal design
- 16 AWG SJT rated cable
- In 3, 6, and 10 foot lengths

**P13A-C13-C14****Application:**

- Extend C13 power cables
- Rack cord management and cord cleanup

**ECONOMY UL LISTED IEC 60320 C13 TO IEC 60320 C14 14 AWG 15 AMP POWER CORDS****Power Extension Cords****CPU'S & DISPLAYS****Features & Benefits:**

- Standard Computer Power Cord rated for 15A
- Power Extension cable for a PC printer or monitor
- Plug Type - IEC-320-C13 to IEC-320-C14
- Universal design
- 14 AWG SJT rated cable
- In 3, 6, and 10 foot lengths

**P15A-C13-C14****Application:**

- Extend C13 power cables
- Rack cord management and cord cleanup

**TRIPPLITE PREMIUM UL LISTED IEC 60320 C19 TO IEC 60320 C20 12 AWG 20 AMP POWER CORDS**

**Power Extension Cords**

**CPU'S & DISPLAYS**



**Features & Benefits:**

- Molded Heavy-Duty Power Cable for up to 20 Amps
- Plug type - IEC 60320 C19 to IEC 60320 C20
- 12AWG SJTW rated cable up to 250 Volts
- UL listed and RoHS Compliant
- 6 feet long

**P036**

**Application:**

- Server applications where more power is needed
- Ideal for Blade Server applications

**ECONOMY NEMA 1-15P TO IEC 60320 C7 APPLIANCE POWER CORDS**

**Appliance Power Cords**

**APPLIANCE POWER CORDS**



**Features & Benefits:**

- Standard Computer Power Cord rated for 10A
- Replacement appliance power cable
- Plug Type - NEMA 1-15P (AC) to IEC-320-C7
- 18 AWG lampcord style bulk cable
- In 3 and 10 foot lengths

**P10A-A115P-C7**

**Application:**

- Replace existing appliance power cord
- Change length for appliance power cords

**TRIPPLITE PREMIUM UL LISTED NEMA 5-15P TO IEC 60320 C13 18 AWG 10 AMP POWER CORDS**

**Appliance Power Cords**

**CPU'S & DISPLAYS**



**Features & Benefits:**

- Standard Computer Power Cord, 1ft 10A
- 1-ft. replacement power cable for a PC, printer, monitor
- Plug Type - NEMA 5-15P (AC) to IEC-320-C13
- Universal design
- 10A, 18awg

**P006**

**Application:**

- Ideal for home, office solutions

**TRIPPLITE PREMIUM UL LISTED NEMA 5-15P TO IEC 60320 C13 14 AWG 15 AMP POWER CORDS**

**Appliance Power Cords**

**CPU'S & DISPLAYS**



**Features & Benefits:**

- Standard Computer Power Cord rated for 15A
- Replacement power cable for a PC printer or monitor
- Plug Type - NEMA 5-15P (AC) to IEC-320-C13
- Universal design
- 14 AWG SJT rated cable
- In 1, 3, and 10 foot lengths

**P007**

**Application:**

- Ideal for home or office power solutions
- Rack cord management and cord cleanup

**ECONOMY UL LISTED NEMA 5-15P TO IEC 60320 C13 18 AWG 10 AMP POWER CORDS**
**Appliance Power Cords**
**CPU'S & DISPLAYS**

**Features & Benefits:**

- Standard Computer Power Cord rated for 10A
- Replacement power cable for a PC printer or monitor
- Plug Type - NEMA 5-15P (AC) to IEC-320-C13
- Universal design
- 18 AWG SJT rated cable
- In 1, 3, and 10 foot lengths

**P10A-15P-C13**
**Application:**

- Ideal for home or office power solutions
- Rack cord management and cord cleanup

**ECONOMY UL LISTED SHIELDED NEMA 5-15P TO IEC 60320 C13 18 AWG 10 AMP POWER CORDS**
**Appliance Power Cords**
**CPU'S & DISPLAYS**

**Features & Benefits:**

- Shielded Computer Power Cord rated for 10A
- Replacement power cable for a PC printer or monitor
- Plug Type - NEMA 5-15P (AC) to IEC-320-C13
- Universal design
- 18 AWG SJT rated cable
- In 6 and 12 foot lengths

**P10A-SH-15P-C13**
**Application:**

- Prevent AC induced EMI from the power component cable

**ECONOMY UL LISTED NEMA 5-15P TO IEC 60320 C13 16 AWG 13 AMP POWER CORDS**
**Appliance Power Cords**
**CPU'S & DISPLAYS**

**Features & Benefits:**

- Standard Computer Power Cord rated for 13A
- Replacement power cable for a PC printer or monitor
- Plug Type - NEMA 5-15P (AC) to IEC-320-C13
- Universal design
- 16 AWG SJT rated cable
- In 1, 3, and 10 foot lengths

**P13A-15P-C13**
**Application:**

- Ideal for home or office power solutions
- Rack cord management and cord cleanup

**ECONOMY UL LISTED NEMA 5-15P TO IEC 60320 C13 14 AWG 15 AMP POWER CORDS**
**Appliance Power Cords**
**CPU'S & DISPLAYS**

**Features & Benefits:**

- Standard Computer Power Cord rated for 15A
- Replacement power cable for a PC printer or monitor
- Plug Type - NEMA 5-15P (AC) to IEC-320-C13
- Universal design
- 14 AWG SJT rated cable
- In 1, 3, and 10 foot lengths

**P15A-15P-C13**
**Application:**

- Ideal for home or office power solutions
- Rack cord management and cord cleanup

**TRIPPLITE PREMIUM UL LISTED NEMA 5-15R TO IEC 60320 C14 18 AWG 10 AMP POWER CORDS**

Appliance Power Cords

CPU'S & DISPLAYS



**Features & Benefits:**

- Heavy Duty Computer Power Cord, 25ft 10A
- 25-ft. power cable extension
- Plug Type - NEMA 5-15P to 5-15R
- Universal design
- 10A, 18awg

**P022**

**Application:**

- Ideal for homeoffice solutions

**ECONOMY UL LISTED NEMA 5-15R TO IEC 60320 C14 18 AWG 10 AMP POWER CORDS**

Appliance Power Cords

CPU'S & DISPLAYS



**Features & Benefits:**

- Standard Computer Power Cord rated for 13A
- Power Extension cable for general purpose power routing
- Plug Type - NEMA 5-15P to NEMA 5-15R
- Universal design
- 16 AWG SJT rated cable
- In 1, 6, 10, 15, and 25 foot lengths

**P10A-15R-C14**

**Application:**

- Power Extension of NEMA 5-15 standard power cables
- Power management and routing

**LIBERTY PREMIUM 5 BNC TO 5 BNC RGBHV VIDEO CABLES**

RGBHV

CPU



**Features & Benefits:**

- 5 BNC Male Plug to 5 BNC Male Plug Connectivity
- Video on 26 AWG high resolution coaxial cables
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-5BNCM-M**

**Application:**

- RGBHV Video, Composite Video, Component Video
- Inter and Intra device interconnection

**KYCON LOCKING S-VIDEO BREAKOUT CABLES**

Appliance Power Cords  
NON-PLENUM



- Features & Benefits:**
- Mini-Din 4 Male to 2 BNC male connectivity
  - Kycon locking Mini-Din 4 plug for extra security
  - UL AWM rated for device interconnection
  - S-Video to Y/C coaxial breakout

**E-LSVM-2BNMCM**

- Application:**
- Secure SV connection in moveable equipment installations
  - Medical Video and video imaging applications
  - Intra-Device equipment hookup

**LIBERTY PREMIUM MOLDED S-VIDEO MINI-DIN TO Y/C BNC FEMALE CABLE**

Appliance Power Cords  
NON-PLENUM



- Features & Benefits:**
- Male S-Video Plug to 2 BNC Jack (Female) Connectivity
  - 26 AWG Stranded mini-High Resolution Coaxial cables
  - 75 Ohm BNC Jacks
  - Durable heavy duty molding and strain relief
  - NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-SVM-2BNCF**

- Application:**
- S-Video conversion to Y/C 2-wire
  - Y/C Video breakout to larger low loss coaxial cables
  - Installations where S-Video has to go through conduit

**LIBERTY PREMIUM MOLDED S-VIDEO MINI-DIN TO Y/C BNC MALE CABLE**

Appliance Power Cords  
NON-PLENUM




- Features & Benefits:**
- Male S-Video Plug to 2 BNC Plug (male) Connectivity
  - 26 AWG Stranded mini-High Resolution Coaxial cables
  - 75 Ohm BNC plugs
  - Durable heavy duty molding and strain relief
  - NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-SVM-2BNMCM**

- Application:**
- S-Video conversion to Y/C 2-wire
  - Y/C Video breakout to larger low loss coaxial cables
  - Installations where S-Video has to go through conduit

**LIBERTY PREMIUM MOLDED S-VIDEO MINI-DIN CABLE**

Appliance Power Cords  
NON-PLENUM



- Features & Benefits:**
- S-Video Mini-DIN 4 pin male to male connectivity
  - 26 AWG Stranded mini-High Resolution Coaxial cables
  - Durable metal shell plugs and strain relief
  - NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-SVM-M**

- Application:**
- S-Video equipment interconnection
  - In-wall S-Video signal routing

**LIBERTY ECONOMY SERIES MOLDED S-VIDEO CABLES**

Appliance Power Cords  
NON-PLENUM



- Features & Benefits:**
- S-Video Mini-DIN 4 pin male to male connectivity
  - 26 AWG Stranded mini-High Resolution Coaxial cables
  - Durable metal shell plugs and strain relief
  - NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**Z100SV**

- Application:**
- S-Video equipment interconnection
  - In-wall S-Video signal routing

**THX® CERTIFIED LIBERTY PREMIUM Z400 SERIES S-VIDEO INTERCONNECT CABLES**

Appliance Power Cords  
NON-PLENUM



**Features & Benefits:**  
• NA

**Z400NSVTHX**

**Application:**  
• NA

**LIBERTY PREMIUM OCC Z500 SERIES S-VIDEO INTERCONNECT CABLES**

Appliance Power Cords  
NON-PLENUM



**Features & Benefits:**  
• Gold Plated Mini DIN plugs with Glossy white enamel  
• Black banded for S-Video  
• Silver Solder and Ohno-Continuous Cast Copper (OCC)  
• Dual Shielded for low and high frequency use  
• Polypropylene silk mesh overall jacket  
• Available in 1.5 meters

**Z500SV**

**Application:**  
• Y/C Video

**LIBERTY MANUFACTURED PLENUM RATED S-VIDEO MALE TO MALE CABLE**

Appliance Power Cords  
PLENUM



**Features & Benefits:**  
• NA

**PSVM-M**

**Application:**  
• NA

**GEPCO BRAND SMPTE 311 HYBRID CABLES WITH LEMO 3K CONNECTORS**

SMPTE Hybrid Fiber Video

**Features & Benefits:**  
• HDC920 W/LEMO 3K PLUG 50'

**GHF92A-0**

**Application:**  
• NA



**HOSA TECHNOLOGY SPEAKER ADAPTER CABLE SPEAKON® FEMALE TO 1/4" FEMALE TS 6" LONG**

**Speaker Cables**



**Features & Benefits:**

- Adapter cable format cable length 6 inches
- Neutrik® speakON to 1/4 TS female connectivity
- 12 AWG 2 Conductor Oxygen Free Copper Bulk Cable
- Intended for Speaker applications, not line level audio

**GSK-112**

**Application:**

- Adapting a Speaker 1/4 plug to SpeakON
- Ideal for stage, touring, and live shows
- Adapting speaker circuits and patching

**HOSA TECHNOLOGY EDGE SPEAKER CABLES 12 AWG 1/4" TS MALE TO 1/4" TS MALE**

**Speaker Cables**



**Features & Benefits:**

- 1/4 TS male to 1/4 TS male connectivity
- Original Neutrik connectors for security and reliability
- 12 AWG Oxygen-Free Copper for maximum signal transfer
- Black PVC jacket for low visibility on stage
- Available lengths: 3,5,10,15,20,25,30,50,75, and 100 feet

**SKJ-200**

**Application:**

- Speaker Cable patching and interconnection
- Ideal for stage shows, studios, and venue support

**HOSA TECHNOLOGY PRO SPEAKER CABLES 14 AWG 1/4" TS MALE TO 1/4" TS MALE**

**Speaker Cables**



**Features & Benefits:**

- 1/4 TS male to 1/4 TS male connectivity
- Rean by Neutrik connectors for security and reliability
- 14 AWG Oxygen-Free Copper for maximum signal transfer
- Black PVC jacket for low visibility on stage
- Available lengths: 3,5,10,15,20,25,30,50,75, and 100 feet

**SKJ-400**

**Application:**

- Speaker Cable patching and interconnection
- Ideal for stage shows, studios, and venue support

**HOSA TECHNOLOGY STANDARD SPEAKER CABLES 16 AWG 1/4" TS MALE TO 1/4" TS MALE**

**Speaker Cables**



**Features & Benefits:**

- 1/4 TS male to 1/4 TS male connectivity
- Metal shelled 1/4 connectors for security and reliability
- 16 AWG Oxygen-Free Copper for maximum signal transfer
- Black PVC jacket for low visibility on stage
- Available lengths: 3,5,10,15,20,25,30,50,75, and 100 feet

**SKJ-600**

**Application:**

- Speaker Cable patching and interconnection
- Ideal for stage shows, studios, and venue support

**HOSA TECHNOLOGY STANDARD SPEAKER CABLES 16 AWG 1/4" TS MALE TO DUAL BANANA**

**Speaker Cables**



**Features & Benefits:**

- 1/4 TS male to Dual Banana Plug connectivity
- Metal shelled 1/4 connectors for security and reliability
- 16 AWG Oxygen-Free Copper for maximum signal transfer
- Black PVC jacket for low visibility on stage
- Intended for high-current applications, no line-level
- Available lengths: 3,5,10,15,20,25,30,50,75, and 100 feet

**SKJ-600N**

**Application:**

- Speaker Cable patching and interconnection
- Ideal for stage shows, studios, and venue support

**HOSA TECHNOLOGY EDGE SPEAKER CABLES 12 AWG SPEAKON FEMALE TO SPEAKON FEMALE**

**Speaker Cables**



**Features & Benefits:**

- SpeakON female to SpeakON female connectivity
- Original Neutrik connectors for security and reliability
- 12 AWG Oxygen-Free Copper for maximum signal transfer
- Black PVC jacket for low visibility on stage
- Available lengths: 3,5,10,15,20,25,30,50,75, and 100 feet

**SKT-200**

**Application:**

- Speaker Cable patching and interconnection
- Ideal for stage shows, studios, and venue support

**HOSA TECHNOLOGY EDGE SPEAKER CABLES 12 AWG SPEAKON FEMALE TO 1/4" TS MALE**

**Speaker Cables**



**Features & Benefits:**

- SpeakON female to 1/4 male connectivity
- Original Neutrik connectors for security and reliability
- 12 AWG Oxygen-Free Copper for maximum signal transfer
- Black PVC jacket for low visibility on stage
- Available lengths: 3,5,10,15,20,25,30,50,75, and 100 feet

**SKT-200Q**

**Application:**

- Speaker Cable patching and interconnection
- Ideal for stage shows, studios, and venue support

**HOSA TECHNOLOGY PRO SPEAKER CABLES 14 AWG SPEAKON FEMALE TO SPEAKON FEMALE**

**Speaker Cables**



**Features & Benefits:**

- SpeakON female to SpeakON female connectivity
- Rean by Neutrik connectors for security and reliability
- 14 AWG Oxygen-Free Copper for maximum signal transfer
- Black PVC jacket for low visibility on stage
- Available lengths: 3,5,10,15,20,25,30,50,75, and 100 feet

**SKT-400**

**Application:**

- Speaker Cable patching and interconnection
- Ideal for stage shows, studios, and venue support

**HOSA TECHNOLOGY PRO SPEAKER CABLES 14 AWG SPEAKON FEMALE TO 1/4" TS MALE**

**Speaker Cables**



**Features & Benefits:**

- SpeakON female to 1/4 male connectivity
- Rean by connectors for security and reliability
- 14 AWG Oxygen-Free Copper for maximum signal transfer
- Black PVC jacket for low visibility on stage
- Available lengths: 3,5,10,15,20,25,30,50,75, and 100 feet

**SKT-400Q**

**Application:**

- Speaker Cable patching and interconnection
- Ideal for stage shows, studios, and venue support



**HOSA TECHNOLOGY STAGE BOX WITH 16 XLR CHANNELS AND 4 1/4" TRS RETURNS**

Stage Boxes with Integrated Cables



**Features & Benefits:**

- 16 x XLR Sends and 4 x 1/4 TRS Returns
- Serviceable, all-metal connectors
- Individually shielded 24/1P OFC conductors
- Heavy-gauge rolled-steel with black enamel textured finish
- High-contrast silk-screened lettering
- Heavy-duty wire mesh hanger/strain relief
- Available in 25, 50, and 100 foot lengths

**SH-16X4**

**Application:**

- Stage Snake Box for audio interconnection
- Ideal for stage shows

**HOSA TECHNOLOGY STAGE BOX WITH 18XLR CHANNELS AND 4 1/4" TRS RETURNS**

Stage Boxes with Integrated Cables



**Features & Benefits:**

- 8 x XLR Sends and 4 x 1/4 TRS Returns
- Serviceable, all-metal connectors
- Numbered leads
- Individually shielded 24/1P OFC conductors
- Heavy-gauge rolled-steel with black enamel textured finish
- High-contrast silk-screened lettering
- Foil-wrapped, heat shrink-protected internal wiring
- Heavy-duty wire mesh hanger/strain relief

**SH-8X4**

**Application:**

- Stage Snake Box for audio interconnection
- Ideal for stage shows

**ECONOMY MOLDED USB 3.0 A MALE TO A MALE**

USB Cables



**Features & Benefits:**

- USB "A" Plug (Male) to "A" Plug (Male) Connectivity
- In-Line format, no panel mount option
- Molded PVC connector housings
- USB 1.1, 2.0 and 3.0 Compliant
- AWM rated cable, not for in-wall use

**E-USBAA**

**Application:**

- USB Patching between panels/plates and Host devices
- Not to exceed 16.5 feet without active extensions

**ECONOMY MOLDED USB 3.0 A MALE TO A FEMALE**

USB Cables



**Features & Benefits:**

- USB "A" Male to "A" female connectivity
- In-Line format, no panel mount option
- Active Booster built in, can daisy chain 3 units
- USB 1.1 and 2.0 Compliant
- AWM rated cable, not for in-wall use

**E-USBAAF**

**Application:**

- Extending USB 2.0 circuits past the 16.5 foot maximum
- Boosting a weakened signal after a passive junction.

**ECONOMY MOLDED USB 3.0 A MALE TO B MALE**

USB Cables



**Features & Benefits:**

- USB "A" male to "B" male connectivity
- Molded PVC connector housings
- USB 1.1, 2.0 and 3.0 Compliant
- AWM rated cable, not for in-wall use

**E-USBAB**

**Application:**

- USB connection from host to remote device
- Not to exceed 16.5 feet without active extensions

**USB 2.0 HI-SPEED ACTIVE EXTENSION CABLE A MALE TO A FEMALE**

USB Cables



**Features & Benefits:**

- Extend USB 2.0 signals pass the 16.5' (5m) limitation
- Works with standard USB 2.0 cables
- Bus powered signal booster
- Daisychain up to 5 cables to extend the signal up to 80'
- The U026-016 provides up to 150mA of power to the connected device


**U026**

**Application:**

- USB 2.0 High Speed Extension
- Remote connection of USB peripherals

**USB TO SERIAL ADAPTER CABLE USB A MALE TO DB9 MALE**

USB Cables



**Features & Benefits:**

- Connect RS-232 Serial devices to USB ports
- Supports data transfer rates up to 230 kbps
- Prolific PL2303HXD-LF Chipset
- Compatible with Windows 98, Windows 98 SE, Windows 2000
- Windows ME, XP, VISTA, 7, 8, 32/64 bit systems
- 2008 Server 32/64, 2012 Server 32/64

**U209-000-R**

**Application:**

- Allow control of Serial devices with USB
- Use of older devices/equipment with new USB technology

**USB 3.0 SUPERSPEED ACTIVE REPEATER CABLE A MALE TO B MALE**

USB Cables



**Features & Benefits:**

- USB "A" Plug (Male) to "B" Plug (Male) Connectivity
- Built in repeater
- In-Line Extension format, no panel mount option
- Molded PVC connector housings
- SuperSpeed USB 3.0, Hi-Speed 2.0, and 1.1 Compliant
- Available in 25 and 36 foot lengths

**U328**

**Application:**

- Active extension of USB Cables beyond the 5m limit
- Connect Host to device up to 25 feet away

**USB 3.0 SUPERSPEED ACTIVE REPEATER CABLE A MALE TO A FEMALE**

USB Cables



**Features & Benefits:**

- Extend a USB 3.0 signal 16 ft. (5 m.)
- Daisy Chain to 33 ft.(10m) by coupling 2 U330-05M together
- Works together with standard USB 3.0 cables
- Provides up to 150mA of power to the connected device
- If more than 150mA of power, use external power
- Accepts a 5V, 2A power supply with a 3.5 x 1.35mm DC jack
- Backward compatible to previous USB generations

**U330**

**Application:**

- Extend a USB 3.0 signal 16.5 ft (5m)
- Supports USB 3.0 SuperSpeed data rates up to 5Gbps

**KEYSPAN HIGH-SPEED USB TO SERIAL ADAPTER USB A MALE TO DB9 MALE**

USB Cables



**Features & Benefits:**

- Keyspan Hi Speed USB Serial Adapter, PC MAC, supports Cisco
- Break Sequence

**USA-19HS**

**Application:**

- NA

CABLES | PRE-MADE & PATCH | VGA | TABLETOP MICRO

**TABLETOP HDMI, VGA AND AUDIO HYBRID CABLES**

VGA Cables

TABLETOP MICRO



**Features & Benefits:**

- Digital HDMI and Analog VGA plus Audio in one cable
- Siamese or SPT type cabling format
- 28 AWG HDMI for superior bandwidth and headroom
- 32 AWG coaxial VGA for WUXGA to 19 feet
- UL and CSA listed product, AWM for non in-wall use
- 10.2 Gbps / 4Kx2K / 3D / Audio Return / CEC / Ethernet

**E-HDVAM-M**

**Application:**

- Tabletop or podium mobile device connection
- Presentation systems and boardroom A/V connectivity
- Inter and Intra device Interconnection

**MICRO VGA AND AUDIO WITH ETHERNET SINGLE CABLE SOLUTIONS**

VGA Cables

TABLETOP MICRO



**Features & Benefits:**

- HDMI "A" Male to "A" Male Connectivity
- Ultra small flexible diameter cable 3.6mm in diameter
- Flexible Polyvinyl Chloride Jacket
- AWM rated, RoHS Compliant
- ATC Certified HDMI(R) High Speed with Ethernet
- 10.2 Gbps / 4Kx2K / 3D / CEC
- Lengths 2m and longer are directional
- 4m length does not support Ethernet

**E-MVGAANM-M**

**Application:**

- HDMI Digital Multimedia Device Interconnection
- Direct rack patching HDMI equipment
- Inter and Intra device Interconnection

**MICRO VGA EXTENSION AND COUPLING CABLE**

VGA Cables

TABLETOP MICRO



**Features & Benefits:**

- Micro-Sized Molding and Cable for small OD and flexibility
- VGA male to female connectivity
- Full 15-Pin VESA EDID and ID/DDC Compliance
- Double Shielded foil and braid overall shield
- Ferrite Beads for EMI Compliance
- Thumbscrew for ease of installation and retention
- UL AWM 20276, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-MVGAM-F**

**Application:**

- RGBHV Video VGA 640x480 up to WUXGA 1920x1200
- Extension and specialty plate/panel connection
- Inter and Intra device interconnection

**LIBERTY MICRO VGA TABLETOP EDID COMPLIANT VGA CABLE**

VGA Cables  
TABLETOP MICRO



- Features & Benefits:**
- Micro-sized molding & cable for small OD & flexibility
  - DE15 Male Plug to DE15 Male Plug Video Connectivity
  - Video & sync on 32 AWG high resolution coaxial cables
  - ID Bit communications & EDID Pin 9 on 28 AWG cabling
  - Full 15-Pin VESA EDID and ID/DDC Compliance
  - Double Shielded foil and braid overall shield
  - Ferrite Beads for EMI Compliance
  - Thumbscrew for ease of installation and retention
  - UL AWM 20276, CSA Type AWM I/II A/B FT1, RoHS Compliant

**E-MVGAM-M**

- Application:**
- RGBHV Video, VGA 640x480 up to WUXGA 1920x1200
  - Tabletop RGBHV with for PC's/laptops
  - Inter and Intra device interconnection

**LIBERTY MICRO VGA EDID COMPLIANT WITH PC STEREO AUDIO CABLE**

VGA Cables  
TABLETOP MICRO



- Features & Benefits:**
- Micro-sized molding & cable for small OD & flexibility
  - DE15 Male Plug to DE15 Male Plug Video Connectivity
  - 3.5mm Male Plug to 3.5mm Male Plug Stereo Audio
  - Video & sync on 32 AWG high resolution coaxial cables
  - ID Bit communications & EDID Pin 9 on 28 AWG cabling
  - Full 15-Pin VESA EDID and ID/DDC Compliance
  - Double Shielded foil and braid overall shield
  - Ferrite Beads for EMI Compliance
  - Thumbscrew for ease of installation and retention
  - 8 & 22 inch Audio leads for routing ease & convenience
  - UL AWM 20276, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-MVGAMAM-M**

- Application:**
- RGBHV video with audio, VGA 640x480 up to WUXGA 1920x1200
  - Tabletop RGBHV with audio Interface for PC's/laptops
  - Inter and Intra device interconnection

**MICRO VGA AND AUDIO WITH USB CONTROL SINGLE CABLE SOLUTIONS**

VGA Cables  
TABLETOP MICRO



- Features & Benefits:**
- Micro-sized molding & cable for small OD & flexibility
  - VGA, 3.5mm audio, and USB A to B male to male connectivity
  - Full 15-Pin VESA EDID and ID/DDC Compliance
  - Double Shielded foil and braid overall shield
  - Ferrite Beads for EMI Compliance
  - Thumbscrew for ease of installation & retention
  - 8 & 22 inch Audio leads for routing ease & convenience
  - UL AWM 20276, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-MVGAPM-M**

- Application:**
- RGBHV video with audio, VGA 640x480 up to WUXGA 1920x1200
  - Tabletop RGBHV with audio Interface for PC's/laptops
  - PC Patching for USB in Tabletop, podium applications
  - Inter and Intra device interconnection

**SPECIAL DEAL MICRO VGA WITH AUDIO USE ONLY PC TO DISPLAY, NO PODIUM USE AUDIO MUST BE CONNECTED!**

VGA Cables  
TABLETOP MICRO



- Features & Benefits:**
- Micro-Sized Molding and Cable for small OD & flexing
  - DE15 Male Plug to DE15 Male Plug Video Connectivity
  - 3.5mm Male Plug to 3.5mm Male Plug Stereo Audio
  - Full 15-Pin VESA EDID and ID/DDC Compliance
  - Thumbscrew for ease of installation and retention
  - UL AWM listed, not for in-wall use

**EMVAM**

- Application:**
- RGBHV video with audio, VGA 640x480 to WUXGA 1920x1200
  - Tabletop RGBHV with audio Interface for PC's/laptops
  - Inter and Intra device interconnection

**LIBERTY MICRO VGA TABLETOP EDID COMPLIANT VGA CABLE**

VGA Video Only Cables  
NON-PLENUM



**Features & Benefits:**

- Micro-sized molding & cable for small OD & flexibility
- DE15 Male Plug to DE15 Male Plug Video Connectivity
- Video & sync on 32 AWG high resolution coaxial cables
- ID Bit communications & EDID Pin 9 on 28 AWG cabling
- Full 15-Pin VESA EDID and ID/DDC Compliance
- Double Shielded foil and braid overall shield
- Ferrite Beads for EMI Compliance
- Thumbscrew for ease of installation and retention
- UL AWM 20276, CSA Type AWM I/II A/B FT1, RoHS Compliant

**E-MVGAM-M**

**Application:**

- RGBHV video, VGA 640x480 up to WUXGA 1920x1200
- Tabletop RGBHV with for PC's/laptops
- Inter and Intra device interconnection

**LIBERTY PREMIUM MOLDED VGA FEMALE TO 5 BNC FEMALE CABLE**

VGA Video Only Cables  
NON-PLENUM



**Features & Benefits:**

- Male VGA female to 5 BNC female Connectivity
- 26 AWG Stranded mini-High Resolution Coaxial cables
- 75 Ohm BNC jacks
- Durable heavy duty molding and strain relief
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-VGAF-5BNCF**

**Application:**

- RGBHV video breakout to larger low loss coaxial cables
- Installations where RGBHV has to go through conduit

**LIBERTY PREMIUM MOLDED VGA FEMALE TO 5 BNC MALE CABLE**

VGA Video Only Cables  
NON-PLENUM



**Features & Benefits:**

- Male VGA female to 5 BNC female Connectivity
- 26 AWG Stranded mini-High Resolution Coaxial cables
- 75 Ohm BNC jacks
- Durable heavy duty molding and strain relief
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-VGAF-5BNCM**

**Application:**

- RGBHV video breakout to larger low loss coaxial cables
- Installations where RGBHV has to go through conduit

**LIBERTY PREMIUM MOLDED VGA MALE TO 5 BNC FEMALE CABLE**

VGA Video Only Cables  
NON-PLENUM



**Features & Benefits:**

- Male VGA male to 5 BNC female Connectivity
- 26 AWG Stranded mini-High Resolution Coaxial cables
- 75 Ohm BNC jacks
- Durable heavy duty molding and strain relief
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-VGAM-5BNCF**

**Application:**

- RGBHV video breakout to larger low loss coaxial cables
- Installations where RGBHV has to go through conduit

**LIBERTY PREMIUM MOLDED VGA MALE TO 5 BNC MALE CABLE**

VGA Video Only Cables  
NON-PLENUM



**Features & Benefits:**

- Male VGA male to 5 BNC female Connectivity
- 26 AWG Stranded mini-High Resolution Coaxial cables
- 75 Ohm BNC plugs
- Durable heavy duty molding and strain relief
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-VGAM-5BNCM**

**Application:**

- RGBHV video breakout to larger low loss coaxial cables
- Installations where RGBHV has to go through conduit

**LIBERTY PREMIUM MOLDED EDID COMPLIANT VGA CABLE**

VGA Video Only Cables  
NON-PLENUM



**Features & Benefits:**

- DE15 Male Plug to DE15 Female Plug Connectivity
- Video and sync on 26 AWG high resolution coaxial cables
- ID Bit communications and EDID Pin 9 on 22 AWG cabling
- Full 15-Pin VESA EDID and ID/DDC Compliance
- Double Shielded foil and braid overall shield
- Ferrite Beads for EMI Compliance
- Thumbscrew for ease of installation and retention
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-VGAM-F**

**Application:**

- Extension of RGBHV Video, VGA 640x480 to WUXGA 1920x1200
- In-wall routing of RGBHV Video in non-plenum installations
- Inter and Intra device interconnection

**LIBERTY PREMIUM MOLDED EDID COMPLIANT VGA CABLE**

VGA Video Only Cables  
NON-PLENUM



**Features & Benefits:**

- VGA male to male connectivity
- 26 AWG Stranded mini-High Resolution Coaxial cables
- Pin 9 EDID VESA power connected
- Durable heavy duty molding and strain relief
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-VGAM-M**

**Application:**

- EDID in-wall VGA signal routing
- Flat Screen, Projector, Video Wall
- Education, Boardroom, Home Theater

**LIBERTY Z100 VGA CABLE**

VGA Video Only Cables  
NON-PLENUM



**Features & Benefits:**

- DE15 Male Plug to DE15 Male Plug Connectivity
- Video and sync on 28 AWG high resolution coaxial cables
- ID Bit communications and EDID Pin 9 on 24 AWG cabling
- Full 15-Pin VESA EDID and ID/DDC Compliance
- Double Shielded foil and braid overall shield
- Ferrite Beads for EMI Compliance
- Thumbscrew for ease of installation and retention
- All Gold Plated Contact Surfaces
- UL AWM 20276, CSA Type AWM I/II A/B FT4, RoHS Compliant

**Z100VGA**

**Application:**

- RGBHV Video, VGA 640x480 up to WUXGA 1920x1200
- Routing of RGBHV Video in non-NEC regulated installations
- Inter and Intra device interconnection

**LIBERTY MANUFACTURED PLENUM VGA MALE TO NON-TERMINATED END WITH C-TEC2 BNC KITTED**

VGA Video Only Cables  
PLENUM



**Features & Benefits:**

- Pre-terminated VGA end to tail connectivity
- 5 Compression style MHR BNC plugs for field termination
- 200 MHz 26 AWG stranded MHR 5-wire RGB cable
- NEC CMP/CL2P, CEC CMP FT6, RoHS Compliant
- Standard lengths 25, 35, 50, 75, and 100 feet

**D-INSTALLKIT-CMP**

**Application:**

- Tight space constraints
- Conduit Pulls
- RGBHV

**LIBERTY MANUFACTURED PLENUM VGA MALE TO NON-TERMINATED END WITH CRIMP BNC'S**

VGA Video Only Cables

PLENUM



**Features & Benefits:**

- Pre-terminated VGA end to tail connectivity
- 5 Crimp style MHR BNC plugs for field termination
- 200 MHz 26 AWG stranded MHR 5-wire RGB cable
- NEC CMP/CL2P, CEC CMP FT6, RoHS Compliant
- Standard lengths 25, 35, 50, 75, and 100 feet

**D-INSTALLKIT-CRP-50**

**Application:**

- Tight space constraints
- Conduit Pulls
- RGBHV

**LIBERTY MANUFACTURED PLENUM RATED VGA MALE TO 5 BNC FEMALE ADAPTER CABLE**

VGA Video Only Cables

PLENUM



**Features & Benefits:**

- DE15 Male (VGA) to 5 BNC Jack (Female) Connectivity
- Full RF Shield, dual shielding.
- 200 MHz Mini-High Resolution 26 AWG Coaxial Construction
- CL2P/CMP Rated Bulk Cable

**D-VGAM-5BNCF**

**Application:**

- RGBHV Video
- Air Plenum, Air Handling, and Plenum space install cable
- Backwards compatible to all non-Plenum NEC Installs

**LIBERTY MANUFACTURED PLENUM RATED VGA MALE TO 5 BNC MALE ADAPTER CABLE**

VGA Video Only Cables

PLENUM



**Features & Benefits:**

- DE15 Male (VGA) to 5 BNC Jack (Female) Connectivity
- Full RF Shield, dual shielding.
- 200 MHz Mini-High Resolution 26 AWG Coaxial Construction
- CL2P/CMP Rated Bulk Cable

**D-VGAM-5BNCFM**

**Application:**

- RGBHV Video
- Air Plenum, Air Handling, and Plenum space install cable
- Backwards compatible to all non-Plenum NEC Installs

**LIBERTY MANUFACTURED PLENUM RATED VGA MALE TO FEMALE CABLE FOR RGBHV**

VGA Video Only Cables

PLENUM



**Features & Benefits:**

- DE15 Male (VGA) to DE15 Female (VGA) Connectivity
- Silver Solder and Full RF Copper Foil EMI Shielding
- RGBHV With Sync ground pin 10 to the shell
- 26 AWG 200 MHz Bandwidth Mini-High Resolution Coaxials
- Flexible Plenum PVC Alloy Jacketing
- Metal Hoods with Thumbscrews
- NEC CMP/CL2P, CEC CMP FT6, RoHS Compliant

**D-VGAM-F**

**Application:**

- Plenum required RGBHV Projector, PC, and Flat Panel cable
- Projector cabling, Boardroom RGBHV cabling

**LIBERTY MANUFACTURED PLENUM RATED VGA MALE TO MALE CABLE FOR RGBHV**

VGA Video Only Cables

PLENUM



**Features & Benefits:**

- DE15 Male (VGA) to DE15 Male (VGA) Connectivity
- Silver Solder and Full RF Copper Foil EMI Shielding
- RGBHV With Sync ground pin 10 to the shell
- 26 AWG 200 MHz Bandwidth Mini-High Resolution Coaxials
- Flexible Plenum PVC Alloy Jacketing
- Metal Hoods with Thumbscrews
- NEC CMP/CL2P, CEC CMP FT6, RoHS Compliant

**D-VGAM-M**

**Application:**

- RGBHV Video
- Air Plenum, Air Handling, and Plenum space install cable
- Backwards compatible to all non-Plenum NEC Installs

**LIBERTY MANUFACTURED PLENUM RATED VGA MALE TO NON-TERMINATED CABLE FOR RGBHV**

VGA Video Only Cables

PLENUM



**Features & Benefits:**

- DE15 Male (VGA) to Non-Terminated blunt end
- Silver Solder and Full RF Copper Foil EMI Shielding
- RGBHV With Sync ground pin 10 to the shell
- 26 AWG 200 MHz Bandwidth Mini-High Resolution Coaxials
- Flexible Plenum PVC Alloy Jacketing
- Metal Hood with Thumbscrews
- NEC CMP/CL2P, CEC CMP FT6, RoHS Compliant

**D-VGAM-T**

**Application:**

- User configured installs where cable length is unknown
- Installer cuts to measure after pull and re-terminates
- Plenum required RGBHV Projector, PC, and Flat Panel cable
- Projector cabling, Boardroom RGBHV cabling

**LIBERTY MANUFACTURED VGA MALE TO FEMALE PLENUM EXTENSION CABLE**

VGA Video Only Cables

PLENUM



**Features & Benefits:**

- VGA male to female connectivity
- 26 AWG Stranded mini-High Resolution Coaxial cables
- Full EDID and plug and Play, pin 9 connected
- Durable heavy duty metal construction
- NEC CL2P/CMP, CSA CMP FT6, RoHS Compliant

**G-VGAM-F**

**Application:**

- Plenum VGA signal extension
- Flat Screen, Projector, with audio installations
- Education, Boardroom, Home Theater

**LIBERTY MANUFACTURED VGA MALE TO MALE PLENUM CABLE**

VGA Video Only Cables

PLENUM



**Features & Benefits:**

- VGA male to male connectivity
- 26 AWG Stranded mini-High Resolution Coaxial cables
- Full EDID and plug and Play, pin 9 connected
- Durable heavy duty metal construction
- NEC CL2P/CMP, CSA CMP FT6, RoHS Compliant

**G-VGAM-M**

**Application:**

- Plenum VGA signal routing
- Flat Screen, Projector, with audio installations
- Education, Boardroom, Home Theater

**PLENUM RATED VGA MALE TO NON-TERMINATED END WITH 5 BNC PLUGS KITTED FOR INSTALL**

VGA Video Only Cables

PLENUM



**Features & Benefits:**

- DE15 Male (VGA) to unterminated Connectivity
- 5 Quicklinx 25 AWG MHR Compression BNC Plugs
- 250 MHz Bandwidth 25 AWG Solid Mini HiRes Coaxial cables
- Support Shrink tubing included for installer assembly
- UL CL2P/CMP and CSA CMP, RoHS Compliant
- All in one package

**P-INSTALLKIT-CMP**

**Application:**

- RGBHV Installations in a plenum environment
- Installer needs to pull cable prior to termination
- VGA to 5 BNC long run RGBHV Application



**LIBERTY VGA & PC AUDIO WITH TRIPLEX AUDIO/VIDEO RCA COMBINATION CABLE**
**VGA Video with Audio Cables**
**NON-PLENUM**

**Features & Benefits:**

- 2 Video channels and 2 audio channels under one jacket
- DE15 Male (VGA) to DE15 Male (VGA) ID/DDC Compliant Video
- RCA Composite Video to RCA Composite Video
- 3.5Mm stereo mini male to 3.5Mm stereo audio male audio
- Left & Right RCA male to Left & Right RCA Male Audio
- 26 Awg 200 MHZ stranded mini-high res coaxial cables
- NEC CL2, CEC CMG FT4, RoHS Compliant

**E-2V2AC3**
**Application:**

- Single Faceplate support for 2 video and 2 audio channels
- Podium Single cable hookup for presentation systems

**TABLETOP HDMI, VGA AND AUDIO HYBRID CABLES**
**VGA Video with Audio Cables**
**NON-PLENUM**

**Features & Benefits:**

- Digital HDMI and Analog VGA plus Audio in one cable
- Siamese or SPT type cabling format
- 28 AWG HDMI for superior bandwidth and headroom
- 32 AWG coaxial VGA for WUXGA to 19 feet
- UL and CSA listed product, AWM for non in-wall use
- 10.2 Gbps / 4Kx2K / 3D / Audio Return / CEC / Ethernet

**E-HDVAM-M**
**Application:**

- Tabletop or podium mobile device connection
- Presentation systems and boardroom A/V connectivity
- Inter and Intra device Interconnection

**LIBERTY MICRO VGA EDID COMPLIANT WITH PC STEREO AUDIO CABLE**
**VGA Video with Audio Cables**
**NON-PLENUM**

**Features & Benefits:**

- Micro-Sized Molding & Cable for small OD & flexibility
- DE15 Male Plug to DE15 Male Plug Video Connectivity
- 3.5mm Male Plug to 3.5mm Male Plug Stereo Audio
- Video & sync on 32 AWG high resolution coaxial cables
- ID bit communications and EDID pin 9 on 28 AWG cabling
- Full 15-Pin VESA EDID and ID/DDC Compliance
- Double Shielded foil and braid overall shield
- Ferrite Beads for EMI Compliance
- Thumbscrew for ease of installation and retention
- 8 & 22 inch Audio leads for routing ease & convenience
- UL AWM 20276, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-MVGAMAM-M**
**Application:**

- RGBHV Video with audio, VGA 640x480 up to WUXGA 1920x1200
- Tabletop RGBHV with Audio Interface for PC's/ Laptops
- Inter and Intra device interconnection

**LIBERTY PREMIUM MOLDED VGA WITH PC STEREO AUDIO CABLE**
**VGA Video with Audio Cables**
**NON-PLENUM**

**Features & Benefits:**

- DE15 Male Plug to DE15 Male Plug Video Connectivity
- 3.5mm Male Plug to 3.5mm Male Plug Stereo Audio
- Video and Sync on 26 AWG high resolution coaxial cables
- ID Bit communications and EDID Pin 9 on 22 AWG cabling
- Full 15-Pin VESA EDID and ID/DDC Compliance
- Double Shielded foil and braid overall shield
- Thumbscrew for ease of installation and retention
- 22 inch Audio leads for routing ease and convenience
- NEC CL2, CSA Type AWM I/II A/B FT4, RoHS Compliant

**E-VGAMAM-M**
**Application:**

- RGBHV Video with audio, VGA 640x480 up to WUXGA 1920x1200
- In-wall routing of RGBHV Video in non-plenum installations
- Inter and Intra device interconnection

**LIBERTY MANUFACTURED VGA TO 5 BNC MALE WITH PC AUDIO PLENUM BREAKOUT CABLE**
**VGA Video with Audio Cables**
**NON-PLENUM**

**Features & Benefits:**


- DE15 Male (VGA) to 5 BNC Plug Video Connectivity
- 3.5mm Stereo Male to Male Audio with 24 inch leads
- 200 MHz Bandwidth 26 AWG MHR Coaxial Construction
- Sync on Coaxial for extremely low loss transmission
- Does not support EDID, ID/DDC Plug and Play. Only RGBHV
- Plenum rated CL2P, CMP bulk cable. RoHS Compliant

**G-VGAMAM-5BNCMAM**
**Application:**

- RGBHV With Audio in Plenum rated install applications
- XGA, WXGA to 50 feet without amplification required
- VGA with PC Audio in Plenum rated install applications
- Single Cable Support for custom faceplates

**LIBERTY Z100 VGA AND 3.5TRS PC STEREO AUDIO CABLE**

VGA Video with Audio Cables  
NON-PLENUM



**Features & Benefits:**

- DE15 Male Plug to DE15 Male Plug Video Connectivity
- 3.5mm Male Plug to 3.5mm Male Plug Stereo Audio
- Video and Sync on 28 AWG high resolution coaxial cables
- ID Bit communications and EDID Pin 9 on 24 AWG cabling
- Full 15-Pin VESA EDID and ID/DDC Compliance
- Double Shielded foil and braid overall shield
- Ferrite Beads for EMI Compliance
- Thumbscrew for ease of installation and retention
- 22 inch Audio leads for routing ease and convenience
- AWM 20276, CSA Type AWM I/II A/B FT1, RoHS Compliant

**Z100VGAA15FT**

**Application:**

- RGBHV Video with audio, VGA 640x480 up to WUXGA 1920x1200
- Routing of RGBHV Video in non-NEC regulated installations
- Inter and Intra device interconnection

**LIBERTY MANUFACTURED VGA+3.5TRS AND TRIPLEX RCA AUDIO/VIDEO PLENUM CABLE**

VGA Video with Audio Cables  
PLENUM



**Features & Benefits:**

- DE15 Male (VGA) Plug to DE15 Male (VGA) Plug RGBHV Video
- RCA Male Plug to RCA Male Plug Composite Video
- 3.5mm Stereo Male Plug to 3.5mm Stereo Male Plug PC Audio
- Dual RCA Male Plug to Dual RCA Male Plug L/R Audio
- All the above under one plenum rated jacket
- 26 AWG stranded Mini-High Resolution Coaxial Cables
- 22 AWG twisted, shielded low capacitance audio pairs
- NEC CMP, CEC CMP FT6, RoHS Compliant
- Custom lengths available upon request

**G-2V2A-B1**

**Application:**

- Single Faceplate Infrastructure cable for plenum runs
- Education, Boardroom, Medical, Commercial A/V installs

**LIBERTY MANUFACTURED VGA+3.5TRS AND TRIPLEX RCA AUDIO/VIDEO PLENUM CABLE**

VGA Video with Audio Cables  
PLENUM



**Features & Benefits:**

- DE15 Male (VGA) to 45-degree DE15 Male (VGA) RGBHV Video
- RCA Male Plug to RCA Male Plug Composite Video
- 3.5Mm stereo male plug to 3.5Mm stereo male plug pc audio
- Dual RCA Male Plug to Dual RCA Male Plug L/R Audio
- All the above under one plenum rated jacket
- 26 AWG stranded Mini-High Resolution Coaxial Cables
- 22 AWG twisted, shielded low capacitance audio pairs
- NEC CMP, CEC CMP FT6, RoHS Compliant
- Custom lengths available upon request

**G-2V2A-C3-45DEG**

**Application:**

- Single Faceplate Infrastructure cable for plenum runs
- Education, Boardroom, Medical, Commercial A/V installs

**LIBERTY MANUFACTURED VGA AND 3.5TRS STEREO AUDIO PLENUM CABLE**

VGA Video with Audio Cables  
PLENUM



**Features & Benefits:**

- DE15 Male to Male (VGA) Video Connection
- 3.5mm Stereo Male to Male Audio with 24 inch leads
- 200 MHz Bandwidth 26 AWG MHR Coaxial Construction
- Sync on Coaxial for extremely low loss transmission
- ID bit, DDC Compatible (Plug and Play) Not EDID 5VDC
- Plenum rated CL2P, CMP bulk cable

**G-VGAMAM-M**

**Application:**

- VGA With Audio in Plenum rated install applications
- XGA, WXGA to 50 feet without amplification required
- VGA with RS-232C in Plenum rated install applications

**HIGH RESOLUTION BNC MALE TO BNC MALE SDI/COMPOSITE VIDEO CABLE**

Video Cables  
NON-PLENUM



- Features & Benefits:**
- BNC Plug (Male) to BNC Plug (Male) Connectivity
  - True 75-Ohm Broadcast BNC Quality Connectors
  - RG6/U Precision Serial Digital Coaxial Cable
  - NEC CMR, CEC CMR FT4, RoHS Compliant

- 18SD-BNCM-M**
- Application:**
- SMPTE SDI Digital Video, AES3id Digital Audio
  - All Analog Video and unbalanced audio formats
  - Broadcast Video Patching and interconnection

**HIGH RESOLUTION BNC MALE TO BNC MALE COMPOSITE VIDEO CABLE**

Video Cables  
NON-PLENUM



- Features & Benefits:**
- Broadcast BNC Male to Male connectivity
  - 4.5 GHz rated cable and connectors
  - NEC CMR, CEC CMR FT4, RoHS compliant

- 20SD-BNCM-M**
- Application:**
- Analog and Digital Video connection
  - SMPTE Video feeds, AES3id Digital Audio
  - SDI, HD-SDI, 3G HD-SDI, DL HD-SDI Video

**HIGH RESOLUTION RCA MALE TO RCA MALE COMPOSITE VIDEO CABLE**

Video Cables  
NON-PLENUM



- Features & Benefits:**
- RCA plug (male) to RCA plug (male) connectivity
  - All gold plated contact surfaces
  - Black metal connector body
  - Serial digital dual shield RG59 size coaxial cable
  - NEC CMR, CEC CMR FT4, RoHS Compliant
  - Many lengths and custom on demand

- 20SD-RCAM-M-**
- Application:**
- Composite video patching, consumer device interconnect
  - Line level unbalanced audio interconnection
  - Inter and intra device A/V patching and routing
  - S/PDIF coaxial audio

**LIBERTY Z100 ECONOMY MOLDED COMPOSITE VIDEO INTERCONNECT FOR NON IN-WALL USE**

Video Cables  
NON-PLENUM



- Features & Benefits:**
- RCA Plug (male) to RCA Plug (male) Connectivity
  - All Gold Plated Contact Surfaces
  - Black Molded Connector body
  - Dual Shield Coaxial Type Construction for Video and Audio
  - Oxygen Free Copper Conductors and Braid Shield
  - RG59 Sized Cable in an economy format
  - UL AWM Listed, RoHS Compliant

- Z100V**
- Application:**
- Composite Video Patching, Consumer device interconnect
  - Line Level Stereo Unbalanced Audio Interconnection
  - Inter and Intra Device A/V Patching and routing
  - S/PDIF Coaxial Audio

**THX® CERTIFIED HOME THEATER GRADE COMPOSITE VIDEO INTERCONNECT FOR NON IN-WALL USE**

Video Cables  
NON-PLENUM



- Features & Benefits:**
- Single RCA male to male connectivity
  - All Gold plated contact surfaces
  - High strand Oxygen Free 75 Ohm RG59 Coaxial cables
  - THX Certification
  - Discontinued, when stock is gone there is no more

- Z300NVTHX**
- Application:**
- Home Theater Composite Video (Y,Pb,Pr)
  - Can also be used for Digital Audio

**THX® CERTIFIED HOME THEATER GRADE COMPOSITE VIDEO INTERCONNECT FOR NON IN-WALL USE**

Video Cables  
NON-PLENUM



**Features & Benefits:**  
• NA

**Z400NVTHX**

**Application:**  
• NA

**THX® CERTIFIED HOME THEATER GRADE COMPONENT VIDEO INTERCONNECT FOR NON IN-WALL USE**

Video Cables  
NON-PLENUM



**Features & Benefits:**  
• Gold Plated RCA plugs with Pearl white enamel  
• Green, Blue, Red banded for Y,Pb,Pr  
• Silver Solder and Ohno-Continuous Cast Copper (OCC)  
• Dual Shielded for low and high frequency use  
• Polypropylene silk mesh overall jacket  
• Available in 2.0, 3.0, and 4.0 meters

**Z500NCVTHX**

**Application:**  
• Component Video, Triplex Audio Video RCA  
• Home Theater, High End Video

**LIBERTY MANUFACTURED HIGH RESOLUTION RCA MALE TO RCA MALE PLENUM VIDEO CABLE**

Video Cables  
PLENUM



**Features & Benefits:**  
• RCA plug (male) to RCA plug (male) connectivity  
• All gold plated contact surfaces with a black metal body  
• Serial digital dual shield RG59 size coaxial cable  
• NEC CMP, CEC CMP FT6, RoHS Compliant  
• Many lengths and custom on demand

**P20SD-RCAM-M**

**Application:**  
• Composite video patching, consumer device interconnect  
• Line level unbalanced audio interconnection  
• Inter and intra device A/V patching and routing  
• S/PDIF coaxial audio

**LIBERTY MANUFACTURED RCA MALE TO RCA MALE PLENUM BASE BAND VIDEO CABLE**

Video Cables  
PLENUM



**Features & Benefits:**  
• RCA male to male connectivity  
• Silver Solder  
• Plenum RG59 base band video cable  
• NEC CMP, CEC CMP FT6, RoHS Compliant

**PRG59-RCAM-M**

**Application:**  
• Low Loss Composite Video  
• Line Level Mono unbalanced Audio  
• S/PDIF Digital Audio

**LIBERTY MANUFACTURED RCA MALE TO NON-TERMINATED END PLENUM BASE BAND VIDEO CABLE**

Video Cables  
PLENUM



**Features & Benefits:**  
• NA

**PRG59-RCAM-T**

**Application:**  
• NA

