



Technical Specifications

Product Line: 22-4C

Description

4 conductor 22 AWG stranded, twisted, and unshielded cable
NEC type CMR and CEC type CMG FT4. Product manufactured compliant to the requirements of UL444 for installations and applications in accordance with NEC articles 725 and 800.

Conductor

22 AWG
7-strand annealed bare copper conductors
Diameter: 0.030" | 0.76mm

Electrical

DC resistance: 16.4 Ω / 1000' | 53.79 Ω /KM
Mutual capacitance: 25.9 pF/FT | 84.95 pF/M
Impedance: 76 Ω
Velocity of Propagation: 55%
Voltage rating: 300V
Maximum current: 2.3A@25 °C

Insulation

Semi-rigid polyvinyl chloride
Wall thickness: 0.006" | 0.15mm
Diameter: 0.041" | 1.04mm

Regulatory

NEC: CMR 75 °C
CEC: CMG FT4 60 °C
EU RoHS 2002/95/EC Compliant

Color Code

Black, Red, White, Green

Packages

Nested Box: 1000' | 305M
Weight: 20 Lbs/1000' | 30 Kg/KM

Assembly

4 conductors twisted
Lay length: 3.0" | 80mm
4.0 twists per foot | 12.5 twists per meter

Installation

Pull Tension: 21 Lbs | 94 N
Bend radius: 1.27" | 33mm unloaded
Bend radius: 2.54" | 66mm loaded

Construct

Ripcord under jacket

Applications

Riser General purpose security and low voltage power
Non-Plenum Class 2 and 3 power

Shield

N/A

Performance

N/A

Jacket

Polyvinyl chloride
Colors: White, Gray
Wall thickness: 0.014" | 0.36mm
Diameter: 0.127" | 3.23mm

Final Outside Diameter (inches)

0.127

Specification Revision Date:

March 4, 2009

