



Technical Specifications

Product Line: **24-4P-P-L5-EN**

Description

4 pair 24 AWG solid, twisted, and unshielded cable

NEC type CMP and CEC type CMP FT6. Third party verified to ANSI/TIA-568C Category 5e performance. Product manufactured compliant to the requirements of UL444 for installations and applications in accordance with NEC articles 725 and 800.

Conductor

24 AWG

Solid annealed bare copper conductors

Diameter: 0.020" | 0.51mm

Electrical

DC resistance: $\leq 28.59 \Omega / 1000'$ | $93.8 \Omega/KM$

DCR Unbalance: $\leq 5.0\%$

Capacitance: 14.0 pF/FT | 45.9 pF/M

Impedance: $100 \pm 15 \Omega$

Propagation Delay (Skew): 45ns/100m MAX

Velocity of Propagation: 71%

Voltage rating: 300V

Pair to ground capacitance Unbalance: $\leq 330 \text{ pF/100M}$

Maximum current: 1.4A@25°C

Insulation

Fluorinated ethylene propylene

Wall thickness: 0.007" | 0.18mm

Diameter: 0.035" | 0.91mm

Regulatory

ANSI/TIA-568-C Category 5e

NEC: CMP 75°C

CEC: CMP FT6 60°C

EU RoHS 2002/95/EC Compliant

Color Code

Pair 1: Orange, White/orange stripe

Pair 2: Blue, White/blue stripe

Pair 3: Green, White/green stripe

Pair 4: Brown, White/brown stripe

Packages

Reel: 1000' | 305M

Weight: 25 Lbs/1000' | 38 Kg/KM

Assembly

Pairs twisted in varying lay lengths with co-extruded like striped conductor

4 twisted pairs cabled on a common axis

Installation

Pull Tension: 25 Lbs | 111 N

Bend radius: 1.95" | 50mm unloaded

Bend radius: 3.90" | 100mm loaded

Plenum cable should be conditioned at room temperature for 24 hours prior to installation and never installed below 32°F | 0°C ambient temperature

Construct

N/A

Applications

Plenum LAN systems 10/100/1000BaseT

Plenum Phone, Voice, Video over IP and security video

BALUN support and media infrastructure

Infrared, audio

Shield

N/A

Performance

LAN: 300 feet

Passive Baluns up to 2500 feet





Technical Specifications

Product Line: 24-4P-P-L5-EN

Jacket

Plenum rated polyvinyl chloride

Colors: Blue, White, Yellow, Green, Gray, Orange, Pink Red,
Violet, Black

Wall thickness: 0.017" | 0.43mm

Diameter: 0.195" | 4.95mm

Final Outside Diameter (inches)

0.195

Specification Revision Date:

February 26, 2006

Category 5e Performance Chart

FREQ (MHz)	Insertion Loss (dB/100m)		NEXT (dB)		PSNEXT (dB)		ACR (dB/100m)		PSACR (dB/100m)		ELFEXT (dB/100m)		PSELFEXT (dB/100m)		RL (dB)	
	568 Max	Typical	568 Min	Typical	568 Min	Typical	568 Min	Typical	568 Min	Typical	568 Min	Typical	568 Min	Typical	568 Min	Typical
0.772	1.8	1.6	67.0	81.0	64.0	68.0	65.2	79.4	62.2	66.4	66.0	69.0	63.0	67.0	N/A	N/A
1.0	2.0	1.7	65.3	79.0	62.3	68.3	63.3	77.3	60.3	66.6	63.8	67.8	60.8	65.8	20.0	20.5
4.0	4.1	3.6	56.3	72.0	53.3	59.3	52.2	68.4	49.2	55.7	51.7	55.8	48.7	53.7	23.0	23.5
8.0	5.8	5.2	51.8	68.0	48.8	54.8	46.0	62.8	43.0	49.6	45.7	49.7	42.7	47.7	24.5	25.0
10.0	6.5	5.9	50.3	67.0	47.3	53.3	43.8	61.1	40.8	47.4	43.8	47.8	40.8	45.8	25.0	25.5
16.0	8.2	7.4	47.3	64.0	44.3	50.2	39.1	56.6	36.1	42.8	39.7	43.7	36.7	41.7	25.0	25.5
20.0	9.3	8.4	45.8	63.0	42.8	48.8	36.5	54.6	33.5	40.4	37.7	41.8	34.7	39.7	25.0	25.5
25.0	10.4	9.4	44.3	61.0	41.3	47.3	33.9	51.6	30.9	37.9	35.8	39.8	32.8	37.8	24.3	24.8
31.25	11.7	10.5	42.9	60.0	39.9	45.9	31.2	49.5	28.2	35.4	33.9	37.9	30.9	35.9	23.6	24.1
62.5	17.0	15.3	38.4	56.0	35.4	41.4	21.4	40.7	18.4	26.1	27.8	31.9	24.8	29.8	21.5	22.0
100.0	22.0	19.7	35.3	53.0	32.3	38.3	13.3	33.3	10.3	18.6	23.8	27.8	20.8	25.8	20.1	20.6
155.0		25.0		51.0		35.4		26.0		10.4		24.0		21.9		19.3
200.0		28.8		48.0		33.8		19.2		5.0		21.8		19.7		18.5
250.0		32.4		47.0		32.3		14.6		-0.1		19.8		17.8		17.8
300.0		35.9		46.0		31.1		10.1		-4.8		18.3		16.2		17.3
350.0		39.3		43.0		30.1		3.7		-9.2		16.9		14.9		16.8

